


40-140 Series Maxwell® Single Handle Lavatory Faucet



Features:

- Ceramic disc cartridge
- Acrylic handle with hot/cold index button
- · Working parts can be easily replaced
- 4" centers for mounting
- 1.5 gpm (5.7 L/min) maximum aerator at 60 psi
- Low lead waterway per NSF/ANSI 372 (previously known as CA AB 1953)



Standards & Certifications:

- NSF/ANSI 61-9
- ASME A112.18.1M
- NSF/ANSI 372
- CSA B125.1
- IAPMO/cUPC
- ICC/ANSI A117.1
- EPA/Watersense
- MASS Code

(152mm) 4 1/2" (114mm) (114mm) (114mm) (114mm) (2-1/2-14NPSM)

Catalog Numbers:

40-140 Less Drain Assembly, Chrome

40-141 Plastic Pop-up, Chrome

40-142 Brass Pop-up, Chrome

Prefixes Available:

None

Suffixes Available:

None

| | (99 | 9mm) |
|---|--|-----------------------|
| | 1/2"Min 51/4" (13mm)Min (133mm) 2 13/16" (71mm) (33mm) | 2 3/8" (60mm) |
| ı | 13/2 32/05 | 2 1/8" (1/8") 4mm) |
| _ | 3 3/8" (86mm) | |
| | 1 1/2-18UNEF / | |
| | Ø1 (Ø32 | 1 <u>/4"</u> 2mm) |

3 7/8"

| Job Name |
|--------------------|
| Date |
| Model Specified |
| Quantity |
| Customer |
| Contractor |
| Architect/engineer |

Gerber Toll Free Technical Support: 888-648-6466 www.gerberonline.com