


4900 Series Mullion

Description: Mullions > 4900 Series

Application: For use with Rim Exit Devices on non-fire rated and fire rated pairs of doors



<p>Certifications</p> <p>Mullion Tube</p> <p>Cylinders</p> <p>Top Fitting</p>	<ul style="list-style-type: none"> - UL/cUL/Warnock Hersey listed for fire rated pairs of doors up to 8 feet (2438 mm) by 8 feet (2438 mm) - UL/cUL listed for up to 3 hours for metal doors and 90 minutes for wood doors - 2" X 3" - 11 Gauge Steel - Solid brass 6-pin rim cylinder sold separately - Deadlock on fire rated device - Latching head allows removal in seconds - Mullion can be locked in place without use of the key 	<p>Fasteners</p> <p>Shims</p> <p>Strikes</p> <p>Finish</p>	<ul style="list-style-type: none"> - 8-32 X 3/4" - Flat head phillips machine screw - 5/16" - 18 X 5/8" - Machine screws - 5/16" - 18 X 1 1/2" - Machine screws - 1/2" and 5/8" shims included - Strikes are supplied with exit device - Fire rated strike and hook kit must be purchased separately - USP - Gray primer only
-----------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------