

# S Thermostatic Trim w/Volume Control





#### **Product Features**

- Thermostatic temperature control
- Volume control for one outlet
- 100° safety stop
- Flow rate 8 GPM @ 44 psi

# **Code Compliance**

This unit meets or exceeds the following:

- ASME A112.18.1 / CSA B125.1
- ASSE 1016
- Listed by IAPMO
- Approved for use in Massachusetts

### **Available Finishes**

Chrome	04230000
Brushed Nickel	04230820
Polished Nickel	04230830

## **Required Accessories**

iBox Universal Plus rough valve 01850181


# **Optional Accessories**

7/8" shallow rough-in set 13596xx0

The measurements shown are for reference only.

Products and specifications shown are subject to change without notice.

Specification sheet revised 8/2010



# 51/4" 51/4"

#### **Product Features**

- ½" male inlet
- Includes escutcheon
- Not for use with oversized or square showerheads

#### **Available Finishes**

Chrome	27411003
Oil Rubbed Bronze	27411623
Brushed Nickel	27411823
Polished Nickel	27411833
Rubbed Bronze	27411923
Polished Brass	27411933

# **Optional Accessories**

C Escutcheon for standard showerarm 04068XX0


The measurements shown are for reference only.

Products and specifications shown are subject to change without notice.

Specification sheet revised 1/2009

# Raindance S 150 AIR 1-Jet Showerhead





#### **Product Features**

- Oversized spray face
- AIR injection technology
- Refreshing full spray
- 96 no-clog spray channels
- Rubit<sup>™</sup> self cleaning system
- 2.5 gpm max.

## **Code Compliance**

This unit meets or exceeds the following:

- ASME A112.18.1
- CSA B125.1
- Listed by IAPMO
- Approved for use in Massachusetts

#### **Available Finishes**

 Chrome
 27486001

 Brushed Nickel
 27486821

The measurements shown are for reference only.

Products and specifications shown are subject to change without notice.

Specification sheet revised 1/2008