



BOLLA 4661OB	
OLDE BRONZE	

WIDTH: 16.0" HEIGHT: 8.3" WEIGHT: 6.0 LBS MATERIAL: METAL GLASS: LIGHT AMBER SEEDY CANOPY: 6" DIA. SOCKET: 1-100W MED MAX HEIGHT: 48.0" MIN HEIGHT: 14.3" CHAIN: 60.0" LEADWIRE: 120.0" DOWN RODS: 3-12" CERTIFICATION: C-US DRY RATED VOLTAGE: 120V UPC: 640665466126 INSTALL UP, INSTALL ON SLOPED OPTIONS: CEILING 90°		
WEIGHT: 6.0 LBS MATERIAL: METAL GLASS: LIGHT AMBER SEEDY CANOPY: 6" DIA. SOCKET: 1-100W MED MAX HEIGHT: 48.0" MIN HEIGHT: 14.3" CHAIN: 60.0" LEADWIRE: 120.0" DOWN RODS: 3-12" CERTIFICATION: C-US DRY RATED VOLTAGE: 120V UPC: 640665466126 INSTALL UP, INSTALL ON SLOPED	WIDTH:	16.0"
MATERIAL: METAL GLASS: LIGHT AMBER SEEDY CANOPY: 6" DIA. SOCKET: 1-100W MED MAX HEIGHT: 48.0" MIN HEIGHT: 14.3" CHAIN: 60.0" LEADWIRE: 120.0" DOWN RODS: 3-12" CERTIFICATION: C-US DRY RATED VOLTAGE: 120V UPC: 640665466126 INSTALL UP, INSTALL ON SLOPED	HEIGHT:	8.3"
GLASS: LIGHT AMBER SEEDY CANOPY: 6" DIA. SOCKET: 1-100W MED MAX HEIGHT: 48.0" MIN HEIGHT: 14.3" CHAIN: 60.0" LEADWIRE: 120.0" DOWN RODS: 3-12" CERTIFICATION: C-US DRY RATED VOLTAGE: 120V UPC: 640665466126 INSTALL UP, INSTALL ON SLOPED	WEIGHT:	6.0 LBS
CANOPY: 6" DIA. SOCKET: 1-100W MED MAX HEIGHT: 48.0" MIN HEIGHT: 14.3" CHAIN: 60.0" LEADWIRE: 120.0" DOWN RODS: 3-12" CERTIFICATION: C-US DRY RATED VOLTAGE: 120V UPC: 640665466126 INSTALL UP, INSTALL ON SLOPED	MATERIAL:	METAL
SOCKET: 1-100W MED MAX HEIGHT: 48.0" MIN HEIGHT: 14.3" CHAIN: 60.0" LEADWIRE: 120.0" DOWN RODS: 3-12" CERTIFICATION: C-US DRY RATED VOLTAGE: 120V UPC: 640665466126 INSTALL UP, INSTALL ON SLOPED	GLASS:	LIGHT AMBER SEEDY
MAX HEIGHT: 48.0" MIN HEIGHT: 14.3" CHAIN: 60.0" LEADWIRE: 120.0" DOWN RODS: 3-12" CERTIFICATION: C-US DRY RATED VOLTAGE: 120V UPC: 640665466126 INSTALL UP, INSTALL ON SLOPED	CANOPY:	6" DIA.
MIN HEIGHT: 14.3" CHAIN: 60.0" LEADWIRE: 120.0" DOWN RODS: 3-12" CERTIFICATION: C-US DRY RATED VOLTAGE: 120V UPC: 640665466126 INSTALL UP, INSTALL ON SLOPED	SOCKET:	1-100W MED
CHAIN: 60.0" LEADWIRE: 120.0" DOWN RODS: 3-12" CERTIFICATION: C-US DRY RATED VOLTAGE: 120V UPC: 640665466126 INSTALL UP, INSTALL ON SLOPED	MAX HEIGHT:	48.0"
LEADWIRE: 120.0" DOWN RODS: 3-12" CERTIFICATION: C-US DRY RATED VOLTAGE: 120V UPC: 640665466126 INSTALL UP, INSTALL ON SLOPED	MIN HEIGHT:	14.3"
DOWN RODS: 3-12" CERTIFICATION: C-US DRY RATED VOLTAGE: 120V UPC: 640665466126 INSTALL UP, INSTALL ON SLOPED	CHAIN:	60.0"
CERTIFICATION: C-US DRY RATED VOLTAGE: 120V UPC: 640665466126 INSTALL UP, INSTALL ON SLOPED	LEADWIRE:	120.0"
VOLTAGE: 120V UPC: 640665466126 INSTALL UP, INSTALL ON SLOPED	DOWN RODS:	3-12"
UPC: 640665466126 INSTALL UP, INSTALL ON SLOPED	CERTIFICATION:	C-US DRY RATED
INSTALL UP, INSTALL ON SLOPED	VOLTAGE:	120V
	UPC:	640665466126

AT HINKLEY, WE EMBRACE THE DESIGN PHILOSOPHY THAT YOU CAN MERGE TOGETHER THE LIGHTING, FURNITURE, ART, COLORS AND ACCESSORIES YOU LOVE INTO A BEAUTIFUL ENVIRONMENT THAT DEFINES YOUR OWN PERSONAL STYLE. WE HOPE YOU WILL BE INSPIRED BY OUR COMMITMENT TO KEEP YOUR 'LIFE AGLOW.'

life AGLOW®