


## assembly instructions


Item No. 58780 / 58782





## Ystart here


## **Drawing 1 - Fixture Mounting**



- 1. Find a clear area in which you can work.
- 2. Unpack fixture and glass from carton.
- 3. Carefully review instructions prior to assembly.
- \*\*\* The construction of this fixture will be accomplished by first mounting the mounting strap to the junction box, making all necessary electrical connections, mounting the fixture to the wall and then installing the glass.
- 1. Prepare mounting strap (A) by threading the two 1 1/4" long mounting screws (B) into the back of the universal strap see **Drawing 1**.
- Be sure the holes into which the screws are threaded match the spacing of holes **(D)** in the back plate **(E)**.
- 2. Attach mounting strap (A) to junction box (J) using two 1" screws (C) provided.

SAFETY WARNING: READ WIRING AND GROUNDING INSTRUCTIONS (I.S. 18) AND ANY ADDITIONAL DIRECTIONS. TURN POWER SUPPLY OFF DURING INSTALLATION. IF NEW WIRING IS REQUIRED, CONSULT A QUALIFIED ELECTRICIAN OR LOCAL AUTHORITIES FOR CODE REQUIREMENTS.

## **Drawing 2 - Glass Installation**



3

Make electrical connections from supply wire to fixture lead wires. Refer to instruction sheet (I.S. 18) and follow all instructions to make all necessary wiring connections. Then refer back to this sheet to continue installation of this fixture.

4

- 1. To mount fixture, slip the two mounting screws **(B)** through the two mounting holes **(D)** in the backplate **(E)** see **Drawing 1**.
- 2. While holding fixture in place, thread the two ball knobs (F) on to the end of the mounting screws (B), and tighten.

5

- 1. To install glass, unthread socket ring (3) from socket (1).
- 2. Slip glass (2) over socket (1).
- 3. Thread socket ring (3) back onto socket (1) to secure glass.
- 4. Fixture can be lamped accordingly at this time.

06.01.13