# S9/S12 **SERIES** VANDAL RESISTANT FIXTURES

Cat. #		Approvals
Job	Туре	

S9 H.I.D.

S9-42F



\$12 H.I.D.

S12-84F

# **APPLICATIONS**

· Ceiling/canopy lighting. Safety and security illumination for parking garage, entrance canopies, stairwells, building eaves.

# **SPECIFICATIONS**

- Die cast aluminum housing with 1/2" conduit hubs.
- Vandal resistant prismatic polycarbonate refractor.
- · Bronze powder paint finish on H.I.D. units.
- · Medium base or compact fluorescent lamps included.
- Typical mounting height ranges from 8 to 15 feet.

#### **LISTINGS**


# S9/S12 Series

UL wet location listed for wall on ceiling mount. Center pin torx screws are standard.





		A	В	C	D	E
<b>S9</b>	H.I.D.	7.09"	8.858"	8.858"	4.1"	8.5"
		180 mm	225 mm	225 mm	104 mm	216 mm
<b>S12</b>	2 H.I.D.	8.858"	12.362"	12.362"	5.3"	11.8"
		225 mm	314 mm	314 mm	135 mm	300 mm



\*CFL units are low profile with no ballast box or conduit hubs. Use B, D & E dimensions above.

# ORDERING INFORMATION

Catalog Number <sup>1</sup>	Description	Voltage	Finish	Weight	
				lbs	kg
	WET LOCATION: CEI	LING/WALL MOUNT COM	IPACT S-9		
S9-42F	42W Fluorescent	120, 208, 240, 277	-	4	(1.8)
S9-70H	70W Pulse Start	120, 208, 240, 277	Bronze	10	(4.5)
S9-70S	70W High Pressure Sodium	120, 208, 240, 277	Bronze	10	(4.5)
	WET LOCATION: CEIL	LING/WALL MOUNT MID-	SIZE S-12		
S12-84F	2X42W Fluorescent	120, 208, 240, 277	-	8	(3.6)
S12-100H	100W Pulse Start	120, 208, 240, 277	Bronze	15	(6.8)
S12-150P	150W Pulse Start	120, 208, 240, 277	Bronze	16	(7.3)
S12-150S	150W High Pressure Sodium	120, 208, 240, 277	Bronze	16	(7.3)

<sup>1</sup> Lamp included on all units.

REPLACEMENT PARTS (order as separate part #, field installed)

Catalog Number	Description	
SM009-LENS	Refractor only for S9 units	
SM012-LENS	Refractor only for S12 units	

Due to our continued efforts to improve our products, product specifications are subject to change without notice.

