



Husqvarna®



RZ4621

For maneuverability, efficiency and convenience in a homeowner zero-turn mower package, the residential series really delivers. True zero-turn mower performance with twin, maintenance-free integrated transmissions, heavy-duty front casters and a rugged tube steel frame. High performance Air Induction cutting decks allow side ejection or optional mulch and collection capability. Convenient control placement, foam padded steering levers and an adjustable seat make these units easy and enjoyable to operate.



BRIGGS STRATTON ENGINE

Briggs & Stratton engines offer durability, dependable starting and the power you need to get the job done.



AIR INDUCTION MOWING TECHNOLOGY

Air is drawn from the top and bottom of the deck, improving grass lift and delivering a superior cut.



MAINTENANCE-FREE TRANSMISSION

Worry free performance with maintenance free, integrated zero-turn transmissions.



WATER HOSE CONNECTION

Facilitates cleaning of the cutting deck. Attach the hose, turn on the water and start the engine and you will get a cleaner deck. For optimum results, clean the mower directly after use.

Features

- No turning radius by individual wheel-drive
- Premium cutting by air induction design deck
- Rugged frame and casters ensure durability
- Comfortable operation
- Adjustable steering levers for optimum comfort
- Convenient control panel placement makes it a breeze to operate.
- Easy-access service points
- Removable foot pan for easy service access
- Hour meter with service minder
- All controls within easy reach
- Adjustment allows fine-tuning of tracking
- Collector available as accessory

Technical data

Engine manufacturer	Briggs & Stratton
Engine name	Endurance Series
Power	21 hp
Cylinder displacement	540 cc
Cylinders	1
Engine cooling	Air
Air Filter type	Standard
Fuel Type	Gasoline
Fuel tank volume (with reserve)	3.5 gal.
Fuel tank location	Side (Single)
Engine lubrication type	Full pressure
Oil capacity	48 fl oz
Oil filter	Yes
Transmission type	Hydrostatic
Transmission manufacturer	Hydro-Gear
Transmission model	EZT
Pump displacement	10 cc
Fan-cooled pumps	Yes
Speed forward, min-max	0-6.5 mph
Speed reverse, min-max	0-3.5 mph
Cutting width	46 inch
Cutting deck type	Stamped
Cutting methods	Collect/Mulch/Side ejection
Cutting deck material	Steel
Deck thickness	13 gauge
Cutting height, min-max (approximate)	1.5 - 4 inch
Cutting height steps	6
Blade engagement	Electric clutch
Clutch rating	105 ft.lb
Blades	2
Blade-tip speed	16600 fpm
Anti-scalp wheels	3
Deck lifting system	Manual, hand operated
Powder-coated cutting deck	Yes
Spindle/mandrel type	Aluminium, vented
Greasable mandrels	Yes
Deck Wash Port	Yes
Seat material	Vinyl
Seat spring	Yes
Seat back height	Medium
Fuel level window	Yes
Hour meter	Digital
Cup holder	Yes
Tire size, front	11x4.5"
Tire size, rear	18x8.5-8"
Wheelbase	41.8"
Base machine, length	75 inch
Base machine, width (chute down)	56 inch
Base machine, width (chute up)	48 inch
Base machine, height	40 inch
Weight	580 lbs
Productivity	2.4 acres/hr
Homeowner Warranty	3 Year Limited
Commercial Warranty	N/A

ARTICLES

966 65 91-01	RZ4621	\$ 2,599.95
966 65 92-01	RZ4621 - CARB Approved	\$ 2,649.95

