



The Next Necessity



Dimensions



Job Specifications



Instant Hot Water Dispensers



H-View-SS

Graceful, clean, transitional design dispenses instant near-boiling 200°F water

Submittal Sheet

- Hot Only Dispenses near-boiling 200°F water
- Durable all metal construction
- Includes 2/3-gallon hot water tank
- · Easy to adjust temperature control
- Tool-free tank connections and dry start protection to ease installation
- Provides 60 cups/hr of near-boiling water
- Fits countertops up to 3" thick
- We Come To You[®] 3-Year In-Home Limited Warranty*
- 115 volts, 750 watts, 6.25 amps
- Available in these designer finishes: chrome and satin nickel

Sample Specification

Instant hot water dispenser(s) shall be InSinkErator Model H-View-SS with 2/3-gallon hot water tank, adjustable temperature from 160°F to 210°F and instant, self-closing hot valve.

Warranty:

3-year parts and in-home service.

* The complete InSinkErator warranty is included in the Care & Use booklet packed with each unit.

US Patent Pending (tank enclosure)

Specifications

Capacity	2/3-gallon hot water tank dispenses 60 cups of 200°F water per hour
Electrical	115 volts A.C., 750 watts, 6.25 amp heating element with grounded three (3) prong plug
Thermostat	Snap-action, adjustable from 160°F to 210°F (factory pre-set at 200°F)
Insulation	Meets U.L. 94HF-1 flammability specification
Valve	Instant, self-closing
Recommended Supply Pressure	30-125 psi
Shipping Weight	Approximately 8.5 lbs.
Required Hole Diameter	1-1/2" standard sink hole









Complies with

USA 1-800-558-1

1-800-558-5700 www.insinkerator.com

Canada

1-800-558-5700 www.insinkerator.ca



The Emerson logo is a trademark and a service mark of Emerson Electric Co.

InSinkErator may make improvements and/or changes in the specifications at any time, in its sole discretion, without notice or obligation and further reserves the right to change or discontinue models.

> ©2013 InSinkErator, a business unit of Emerson Electric Co. All Rights Reserved.

HWD448-13F-45-10

Printed in USA