

ASSEMBLY & INSTALLATION INSTRUCTIONS FOR #25722

Please read carefully and save these instructions, as you may need them at a later date.

CAUTION

Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the installation instructions.

ASSEMBLY AND INSTALLATION

- 1. Measure the distance between the 2 holes at the MIRROR FRAME(12), then mark the hole locations on your wall, drill 2 holes, insert the PLASTIC ANCHOR(11) into the wall then screw the MOUNTING SCREW(10) into the PLASTIC ANCHOR(11). You must leave ¼" of the screw head showing so you can hang up the mirror
- 2. Attach the BLACK SUPPLY WIRE (4) to the SMOOTH (or BLACK) FIXTURE LEAD WIRE (5) by using the WIRE CONNECTOR (1). At the same manner, attach the WHITE SUPPLY WIRE (3) to the RIBBED (or WHITE) FIXTURE LEAD WIRE (6), attach the FIXTURE GROUND WIRE (7) to the SUPPLY GROUND WIRE (3) using a WIRE CONNECTOR (1). Place wiring and connections inside the OUTLET BOX (1).
- 3. Hang up the MIRROR by sliding the holes at the MIRROR FRAME(12) over the MOUNTING SCREW(10).
- 4. Slide the GLASS SHADE(14) over the SOCKET(13), secure with the SOCKET RING(15).
- 5. Screw light bulbs into the sockets and make sure they do not exceed the maximum wattage specified on the fixture's wattage rating label, MAXIMUM 100W.

ASSEMBLY AND INSTALLATION (Continued)

