




TM209

RECESSED LIGHTING
4" APERTURE LINE VOLTAGE TRIMS

Type	
Project	
Catalog No.	



CATALOG INFORMATION

MODEL	TRIM FINISH
TM209	AB - Antique Bronze
	ST - Satin Chrome
	WH - White

Ordering Instructions
Example: **MODEL** - **FINISH**
TM209 - ST

DESCRIPTION

- Recessed Lighting – Flat Showe Trim With Frosted Glass 4" aperture Line Voltage trim.
- Use PAR16, PAR20 120V 50W Max.
- Ideal for use in ceilings, cabinets and displays.
- Includes gasket for use in damp locations
- Dimensions: 3-5/8" A x 5" Ø
- Listings: UL and C-UL listed.

COMPATIBLE LINE VOLTAGE HOUSINGS



RS2000B
Non-IC Universal Housing for New Construction
PAR16/20 120V 50W
Dimensions: 5-1/4"W x 8"L x 5-1/2"D
Hanger Bars: adj. 14-1/2" ~ 24-1/2"
Cutout: 4-3/8"Ø



RS2000IC
IC Housing for New Construction
PAR16/20 120V 50W
Dimensions: 5-1/4"W x 8"L x 6"D
Hanger Bars: adj. 14-1/2" ~ 24-1/2"
Cutout: 4-3/8"Ø



RS2000R
Non-IC Housing for Remodel
PAR16/20 120V 50W
Dimensions: 4-5/8"W x 12"L x 5-1/2"D
Cutout: 4-3/8"Ø

COMPATIBLE LINE VOLTAGE HOUSINGS



RS2000BA
Non-IC Airtight Universal Housing for New Construction
PAR16/20 120V 50W
Dimensions: 5-1/4"W x 8"L x 5-1/2"D
Hanger Bars: adj. 14-1/2" ~ 24-1/2"
Cutout: 4-3/8"Ø



RS2000ICA
IC Airtight Housing for New Construction
PAR16/20 120V 50W
Dimensions: 5-1/4"W x 8"L x 6"D
Hanger Bars: adj. 14-1/2" ~ 24-1/2"
Cutout: 4-3/8"Ø



RS2000RA
Non-IC Airtight Housing for Remodel
PAR16/20 120V 50W
Dimensions: 4-5/8"W x 12"L x 5-1/2"D
Cutout: 4-3/8"Ø