




SS SINGLE SPEED HEAVY DUTY ELECTRIC CHAIN HOIST

Designed for commercial and industrial applications the JET Single Speed Electric Hoists are easy to install, inspect, and maintain. The SS Hoist is equipped with a heavy duty ventilated motor available in a range of HP from 7/8 to 2-1/7. Gear trains feature lifetime lubrication eliminating the need for oil changes. All models come standard with slip clutch overload protection, chain containers and drop forged, heat treated hooks that swivel 360 degrees for easy rigging. Single phase units feature a solid state starting switch that eliminates the mechanical centrifugal mechanism and reversing switch. Quick connect wiring for power and push button controls allow for quick set-up while the DC electro-magnetic brake secures loads even if power is interrupted.

For added convenience and versatility equip the SS Series Electric Hoists with a JET ET series Electric Trolley. Available in a variety of capacities the ET Electric Trolley features the same quick-connect cords as the SS Electric Hoists allowing for fast set-up and installation.





SS SERIES, SINGLE SPEED HEAVY-DUTY ELECTRIC CHAIN HOISTS

- Designed for commercial and industrial applications
- 1/2-ton to 5-ton capacities, single or three phase models
- 10', 15' and 20' lifts standard, custom length lifts available
- Easy to install, inspect and maintain
- Totally enclosed steel plate construction with a durable powder coat finish
- Gear train features lifetime lubrication, no oil changes required
- Heavy-duty ventilated motor with thermal overload protection or reverse phase protection
- Single phase models feature thermal overload protection
- Three phase models feature reverse phase protection
- Can be operated on 50Hz power with 16% reduction in lifting speed
- Equipped with heavy-duty chain container
- Reliable DC electromagnetic brake holds the load even if power is interrupted
- Quick-connect wiring for power and push button controls
- Upper and lower limit switches prevent over-travel

STOCK NUMBER	MODEL NUMBER	STANDARD LIFT	HEADROOM (IN)	DUTY CYCLE	DUTY CYCLE RATING	LIFTING SPEED/ FT PER MINUTE	MOTOR OUTPUT (HP)	RATED AMPS 115V	RATED AMPS 230V	LOAD CHAIN DIAMETER (MM)	NUMBER OF FALLS	GROSS WEIGHT (LBS)
1/2 TON, 1 PHASE												
121100	1/2SS-1C-10	10ft	20 3/16	25%	H3	19.7	7/8	12.6	6	6.3x19	1	108
121150	1/2SS-1C-15	15ft	20 3/16	25%	H3	19.7	7/8	12.6	6	6.3x19	1	112 1/2
121200	1/2SS-1C-20	20ft	20 3/16	25%	H3	19.7	7/8	12.6	6	6.3x19	1	114 1/2
1 TON, 1 PHASE												
111000	1SS-1C-10	10ft	24 7/16	25%	H3	19.7	1-3/4	20.8	10	8x24	1	170
111500	1SS-1C-15	15ft	24 7/16	25%	H3	19.7	1-3/4	20.8	10	8x24	1	174
112000	1SS-1C-20	20ft	24 7/16	25%	H3	19.7	1-3/4	20.8	10	8x24	1	181
2 TON, 1 PHASE												
211000	2SS-1C-10	10ft	28 1/8	25%	H3	9.8	1-3/4	20.8	10	8x24	2	185
211500	2SS-1C-15	15ft	28 1/8	25%	H3	9.8	1-3/4	20.8	10	8x24	2	196
212000	2SS-1C-20	20ft	28 1/8	25%	H3	9.8	1-3/4	20.8	10	8x24	2	205
3 TON, 1 PHASE												
311000	3SS-1C-10	10ft	31 1/2	25%	H3	6.6	1-3/4	20.8	10	8x24	3	216
311500	3SS-1C-15	15ft	31 1/2	25%	H3	6.6	1-3/4	20.8	10	8x24	3	231 1/2
312000	3SS-1C-20	20ft	31 1/2	25%	H3	6.6	1-3/4	20.8	10	8x24	3	244 1/2
5T, 1 PHASE												
511000	5SS-1C-10	10ft	30 11/16	25%	H3	4.9	1-3/4	22	10.5	8x24	4	236
511500	5SS-1C-15	15ft	30 11/16	25%	H3	4.9	1-3/4	22	10.5	8x24	4	255 1/2
1/2T, 3 PHASE												
								RATED AMPS 230V	RATED AMPS 460V			
123100	1/2SS-3C-10	10ft	20-3/16	30%	H3	31.5	1-1/5	3.5	1.8	8x24	1	99
123150	1/2SS-3C-15	15ft	20-3/17	30%	H3	31.5	1-1/5	3.5	1.8	8x24	1	103 1/2
123200	1/2SS-3C-20	20ft	20-3/18	30%	H3	31.5	1-1/5	3.5	1.8	8x24	1	106
1 TON, 3 PHASE												
131000	1SS-3C-10	10ft	24 7/16	30%	H3	24.8	2-1/7	5.9	3	8x24	1	158 1/2
131500	1SS-3C-15	15ft	24 7/16	30%	H3	24.8	2-1/7	5.9	3	8x24	1	163
132000	1SS-3C-20	20ft	24 7/16	30%	H3	24.8	2-1/7	5.9	3	8x24	1	170
2 TON, 3 PHASE												
231000	2SS-3C-10	10ft	28 1/8	30%	H3	12.4	2-1/7	5.9	3	8x24	2	174
231500	2SS-3C-15	15ft	28 1/8	30%	H3	12.4	2-1/7	5.9	3	8x24	2	185
232000	2SS-3C-20	20ft	28 1/8	30%	H3	12.4	2-1/7	5.9	3	8x24	2	194
3 TON, 3 PHASE												
331000	3SS-3C-10	10ft	31 1/2	30%	H3	8.3	2-1/7	5.9	3	8x24	3	205
331500	3SS-3C-15	15ft	31 1/2	30%	H3	8.3	2-1/7	5.9	3	8x24	3	220 1/2
332000	3SS-3C-20	20ft	31 1/2	30%	H3	8.3	2-1/7	5.9	3	8x24	3	233 1/2
5 TON, 3 PHASE												
531000	5SS-3C-10	10ft	30 11/16	30%	H3	6.2	2-1/7	5.9	3	8x24	4	225
531500	5SS-3C-15	15ft	30 11/16	30%	H3	6.2	2-1/7	5.9	3	8x24	4	244 1/2