



Catalog Number
Notes
Type

Contractor Select™

FMLR

Switchable White LED Low Profile Flush Mount 11" Round with Interchangeable Trim



**FMLR 11IN
Black Trim**



**FMLR 11IN
White Trim**

The round low profile 11in. LED Flush Mount features an acrylic diffuser with a sleek, compact design with a touch of modern elegance. A white and black trim ring included to interchange the design to compliment any decor. An integrated 5CCT switch (2700K/3000K/4000K/5000K) allows the end user to fine-tune the feel of their space to insure the right amount of light.

FEATURES:

- Easy-latch secures diffuser to housing, ceiling mount only
- Ideal for new construction or renovation in residential single and multi-family applications as well as light commercial
- Ideal for foyers, hallways, bedrooms, stairways and utility rooms
- Installs directly into industry standard junction boxes
- Suitable for use in closets, compliant when installed to NFPA® 70 NEC® Section 410.16 (A)(1) and (C)(1)



Catalog Number	UPC	Description	Lumens	Input Watts	CCT	CRI	Voltage	Trim Ring Finish	Pallet qty.
FMLR 11IN SWWS 90CRI WBT M4	00196183681843	11" Round Flush Mount with Interchangeable Trim	1200L	18W	2700K/3000K/3500K/4000K/5000K	90	120V	White/Black Trim Ring	144




JBOX Compatibility

	3-1/2" Octagon Box Steel	4" Drawn Octagon 1-1/2" Deep Steel	3-1/2" Drawn Round Ceiling Pan Steel / Old Work	4" Round Plastic / New York	4" Drawn Round Ceiling Pan Steel	4" Round Plastic / New Work	4" Dia. Ceiling Box With Bar Plastic / New York
Exterior LXWXH	3.2" x 3.2" x 1.55"	3.54" x 3.54" x 1.55"	3.38" Rd. x 0.5" Dep.	4" Dia. x 2.3"	4" Dia. x 0.5" Dep.	4" Dia. x 2.375"	14.5" x 4.5" x 4"
Mounting Dimension	2.75"	3.5"	2.75"	2.75" / 3.5"	3.5"	2.75" / 3.5"	2.75" / 3.5"
Fixture	JSBT 4IN/ JSBT 6IN	JSBT 6IN	JSBT 4IN/ JSBT 6IN	JSBT 4IN/ JSBT 6IN	JSBT 6IN	JSBT 4IN/ JSBT 6IN	JSBT 4IN/ JSBT 6IN

	4" Square Box*	WiringPro 4" Square Box*	Iberville 4" Octagonal Box*
Exterior LXWXH	4" x 4" x 1.5"	4" X 4" X 1.5"	4" x 4" x 1.5"
Mounting Dimension	4"	4"	4"
Fixture	JSBT 4IN	JSBT 4IN	JSBT 4IN

* When ordering these junction boxes for Canada requires JSBTADAPTR 4IN CNDA M50.

Canadian 4IN J-Box Bracket



JSBTADAPTR 4IN CNDA M50

Dimmer Compatibility

Forward Phase Dimmers	Reverse Phase Dimmers	Acuity Brands Dimmers
Lutron Maestro Rocker style 120V 600W/MACL-153M/ STCL-153	Lutron Diva ELV® single pole 120V 300W/DVELV-300P	Acuity SensorSwitch® Forward phase paddle dimmer/WPD WH
Lutron RadioRa 250W Resi Dimmer/RRD-PRO	Lutron Maestro ELV® single pole 120V 600W/MAELV-600	
Lutron Vive Wireless dimmer w/ neutral 120V 600W/MRF2S-6ND	Lutron Vive® Wireless Reverse-phase 120V 600W/MRF2S-6ELV	
Lutron Caseta Wireless in-wall 150W/PD-6WCL	Lutron Caseta® Reverse-Phase 120V 150W/PD-SNE	
Leviton SureSlide INC 3-way 120V 600W/6674-10W		
Leviton Illumatech® INC single pole 120V 600W/IPL06-10Z		

LIGHTING PERFORMANCE DATA DONNÉES SUR LE RENDEMENT DE L'ÉCLAIRAGE	
Light Appearance (CCT) Aspect de la lumière (CCT)	
2700K soft white blanc doux	1217 lumens 70 lumens per watt
3000K warm white blanc chaud	1273 lumens 74 lumens per watt
3500K neutral white blanc neutre	1300 lumens 75 lumens per watt
4000K cool white blanc froid	1313 lumens 76 lumens per watt
5000K daylight blanc neutre	1326 lumens 77 lumens per watt
Watts	17.2
Color Accuracy (CRI) Précision des couleurs (CRI)	90



Specifications

INTENDED USE:

The Juno FMLR Round Indoor Flush Mount comes in 11" size and provides a modern aesthetic, at a low cost, with an easy installation, perfect for both contractors and DIYers. The FMLR ships as matte white but includes a black interchangeable trim in the package to bring a design element to match with any desired aesthetic. Additionally, the FMLR features a switch directly on the product that allows you to choose your desired color temperature.

CONSTRUCTION:

Low profile white acrylic diffuser and steel pan • Milky white acrylic, diffuser dome lens conceals the LEDs from direct view and provides uniform lens luminance.

ELECTRICAL:

Accommodates 120 volts AC at 60Hz • 90 CRI minimum • Dimmable with most standard magnetic low voltage and electronic low voltage dimmers.

JUNCTION BOX MOUNTING:

The driverless FMLR installs directly into industry standard junction boxes that requires no separate mounting bracket for installation • Compatible boxes include 3-1/2" and 4" octagon junction boxes (1-1/2" minimum depth), round mud rings with 2-3/4" mounting centers, and 3" & 4" diameter non-metallic boxes • Provides fast installation of fully assembled fixture to JBox • Suitable for ceiling mount • Suitable for use in closets, compliant when installed to NFPA® 70 NEC® Section 410.16 (A)(1) and (C)(1).

LIFE:

High performance, long functional life of 50,000 hrs (L70).

LISTINGS:

CSA certified to US and Canadian safety standards • ENERGY STAR® Certified • Damp location listed • Certified to the high efficacy requirements of California T24 JA8-2022.

WARRANTY:

5-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at: www.acuitybrands.com/support/warranty/terms-and-conditions

Note: All reports are based on published industry procedures; actual performance may differ as a result of the end-user environment and applications.

All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.

Dimensions

	Width	Depth	Lens Opening
FMLR 11IN	11.05	2.81	11

All dimensions are inches (centimeters) unless otherwise indicated.

