

# WALDEN LED

ARCHITECTURAL BRONZE™ OR  
TEXTURED BLACK FINISH



**A** | **49550 AZLED**  
Indoor/Outdoor Wall  
ADA Compliant



**A** | **49550 BKTLED**  
Indoor/Outdoor Wall  
ADA Compliant



**B** | **49551 AZLED**  
Indoor/Outdoor Wall  
ADA Compliant



**B** | **49551 BKTLED**  
Indoor/Outdoor Wall  
ADA Compliant

Clear Glass with  
Inside Etch

Provides Up and  
Down Lighting



These devices  
comply with part 15  
of the FCC Regulations.

## LED OUTPUT

49550 AZLED/ BKTLED	720 LUMENS*, 10 WATTS, 3000 KELVIN, CRI 90, 35K LIFE
49551 AZLED/ BKTLED	1440 LUMENS*, 20 WATTS, 3000 KELVIN, CRI 90, 40K LIFE

\*Initial Lumens. Visit [kichler.com](http://kichler.com) for recent performance and certification data.

ALUMINUM  
CONSTRUCTION

## WALDEN LED

	ITEM #	FINISH	LIGHT SOURCE	W	H	EXT.	HCWO	NOTES
A	49550 AZLED / 49550 BKTLED	AZT, BKT	10W	5	7.5	3.75	3.75	Dimmable
B	49551 AZLED / 49551 BKTLED	AZT, BKT	20W	5	12	3.75	6	Dimmable.

Measurements shown in inches. U.S. & Canada Patent Pending.



These devices  
comply with part 15  
of the FCC Regulations.

# LED WALL

TEXTURED ARCHITECTURAL BRONZE™  
OR TEXTURED BLACK FINISH



**A** | **11250 AZT30**  
Indoor/Outdoor Wall



**A** | **11250 BKT30**  
Indoor/Outdoor Wall



**C** | **11077 AZT**  
Indoor/Outdoor Wall



**B** | **11251 AZT30**  
Indoor/Outdoor Wall



**B** | **11251 BKT30**  
Indoor/Outdoor Wall



**C** | **11077 BKT**  
Indoor/Outdoor Wall

## LED OUTPUT

11077 AZT/BKT	400 LUMENS*, 15 WATTS, 3000 KELVIN, CRI 90, 40K LIFE
11250 AZT30/ 11250 BKT30	350 LUMENS*, 10 WATTS, 3000 KELVIN, CRI 80, 40K LIFE
11251 AZT30/ 11251 BKT30	550 LUMENS*, 15 WATTS, 3000 KELVIN, CRI 80, 40K LIFE

\*Initial Lumens. Visit [kichler.com](http://kichler.com) for recent performance and certification data.

## LED WALL

CAST ALUMINUM  
CONSTRUCTION

	LED ITEM #	FINISH	LIGHT SOURCE	W	H	EXT.	HCWO	NOTES
<b>A</b>	11250 AZT30 / 11250 BKT30	AZT, BKT	(1) 10W	5	7	6.5	3.25	
<b>B</b>	11251 AZT30 / 11251 BKT30	AZT, BKT	(2) 15W	5	12	6.5	6.25	
<b>C</b>	11077 AZT30 / 11077 BKT30	AZT, BKT	(1) 15W	5	5.5	6	2.75	

Measurements shown in inches.

# OUTDOOR WALL

ASSORTED FINISHES



A | 9234 AZ  
Outdoor Wall



Brushed  
Alluminum

A | 9234 BA  
Outdoor Wall



A | 9234 WH  
Outdoor Wall



B | 9236 AZ  
Outdoor Wall



C | 9834 WH  
Outdoor Ceiling

## OUTDOOR WALL

ITEM #	FINISH	INCAND. BULB	W	H	EXT.	HCWO	NOTES
A 9234	AZ, BA, WH	(1) 65W (M) BR-30	4.75	7	7	3.5	W C E 0D (13-15W CFL)
B 9236	AZ	(1) 120W (M) BR-40	6	7.75	8.5	4	W C E 0D (13-15W CFL)
C 9834	WH	(1) 65W (M) BR-30 ❖	4.5	8.5	---	---	D E 0D (23-30W CFL)
D 9244	AZ, BA, WH	(2) 65W (M) BR-30	4.75	12	7	6	D E 0D (13-15W CFL)
E 9246	AZ, BA, WH	(2) 120W (M) BR-40	6	15	8.5	7.5	D E 0D (23-30W CFL)

Measurements shown in inches.



**D** | 9244 AZ  
Outdoor Wall



**D** | 9244 BA  
Outdoor Wall

Brushed  
Aluminum



**D** | 9244 WH  
Outdoor Wall



**E** | 9246 AZ  
Outdoor Wall



**E** | 9246 BA  
Outdoor Wall



**E** | 9246 WH  
Outdoor Wall

### LENS ACCESSORIES

9534 BK

GLASS LENS USE WITH  
9234, 9244

9536 BK

GLASS LENS USE WITH  
9236, 9246

Convert open top units to outdoor applications. Heat-resistant glass lens with black frame.



9534 BK



9536 BK

### BRIGHTNESS CONTROL ACCESSORIES

9544 BK

GROOVED BAFFLE  
USE WITH 9234, 9244

9546 BK

GROOVED BAFFLE  
USE WITH 9236, 9246

Grooved black plastic baffles achieve low, even surface brightness.



9544 BK



9546 BK