

# 4U SERIES - 120V XENON

Each fixture features product extenders that help dissipate possible bulb heat away from the underside of the cabinet.



**4U120X22**  
shown in **NIT** Textured Nickel

## Select Appropriate Light Fixture Size and Finish

### 4U120X08 BZT, NIT, WHT

- 8" L x 4.5" W x 1.1" H
- 1 Bulb
- 20 Watts

### 4U120X12 BZT, NIT, WHT

- 12" L x 4.5" W x 1.1" H
- 2 Bulb
- 40 Watts

### 4U120X22 BZT, NIT, WHT

- 22" L x 4.5" W x 1.1" H
- 3 Bulb
- 60 Watts

### 4U120X30 BZT, NIT, WHT

- 30" L x 4.5" W x 1.1" H
- 4 Bulb
- 80 Watts

## Under Cabinet Accessories (optional)

### 10571 BK, WH

- 9" Interconnect cable

### 10572 BK, WH

- 14" Interconnect cable

### 10573 BK, WH


- 21" Interconnect cable

### 10570 BK, WH

- Wire module
- 7-<sup>3</sup>/<sub>4</sub>" L x 2-<sup>5</sup>/<sub>16</sub>" W x 1" H

### 10588 SI

- Duplex BX cable connector



### 10589 SI (included with fixture)

- Connector for NM & BX cable



### 6UCORD BK, WH

- 60" under-cabinet interconnect prong cord



### 12090 CLR

- Replacement bulb
- 120V, 20 Watt Xenon, clear

## AVAILABLE FINISHES



**BZT** Textured Bronze



**NIT** Textured Nickel



**WHT** Textured White

## BACK MOUNT



## PRODUCT BENEFITS:

- Xenon light source (2,500 hrs.)
- High-low, on-off switch
- Durable powder coat finish
- Dimmable with standard wall dimmer
- 3-year residential warranty

## INSTALLATION BENEFITS:

- Captive screws for quick installation
- Direct wire and linkable
- 1" profile, 4 1/2" depth
- 1/4" extenders help to dissipate heat