

Ferron

As sleek and aerodynamic as a hightech propeller, Ferron[™] employs pure physics to create robust amounts of air. The streamlined motor housing and contoured blades work together to fill a room with comfort.





Shown: 3001600BB Oil Brushed Bronze[™] Finish with Oil Brushed Bronze[™] Blades

60" Ferron™





INCLUDED FEATURES

Blades (2) Included - 14° Pitch - 60" Sweep - Non-Reversible - Polycarbonate Downrods 6" Downrod with 1" (O.D.) Downlight N/A Downlight Glass N/A Optional Downlight N/A Uplight N/A Uplight Glass N/A Low Ceiling Adaptable No Control 6-Speed DC CoolTouch[™]

FAN FEATURES

MOTOR FEATURES

Motor Size/Type DC-125 Amps 0.43 on High RPM 115 on High Energy Star No

Mounting Slope – Pitch 30° or 7/12

Lead Wire 78" cETL Listed Indoor Hanging Weight 16.70 lbs. Body Material Steel Warranty Limited Lifetime

6-SPEED DC COOLTOUCH™ 6 Forward Speeds & Reverse Lights On/Off with Full Range Dimming Motor Off No more than two fans on one circuit O PTIONAL CONTROLS O PTIONAL CONTROLS 3700360WHTR 370036ALMTR 6-SPEED DC WALL TRANSMITTER

INCLUDED CONTROLS

COORDINATING LIGHTING

To see the complete $\mathsf{Roswell}^{^{\scriptscriptstyle \infty}}$ Collection visit Kichler.com.



Oval Chandelier/Pendant 43303OZ

HANGING MEASUREMENTS

6" DOWNROD Fixture Drop Blade Drop Housing (from ceiling) (width)			Ceiling Canopy (width)	$ \begin{array}{c c} -D \rightarrow \\ \hline \\ A & B & C \\ \hline \\ & \\ \hline \\ \hline \end{array} $
A: 15.92"	B: 15.37"	C: 7.25"	D: 5.90"	
airflow	USAGE EF 31 Vatts on High	NCE AIRFLOW FFICIENCY 206 Cubic Ft. Per Minute Per Watt		HIGH EFFICIENCY DCC MOTOR

