

## Gentry LED

Massive in scale and size, Gentry knows how to make an impact – both visually and with impressive airflow. The nine-blade design creates a stunning visual effect on or off. Your choice of industrial era-inspired finish combinations provide styles that fit with modern, classic or rustic settings. The LED light source provides 1,600 lumens of output – about the equivalent of a 150watt incandescent light bulb – for terrific ambient light.





Shown: 300285AVI Anvil Iron Finish, Etched Cased Opal Glass, with Distressed Antique Gray Blades

## 85" Gentry XL LED



300285DBK Distressed Black Finish Walnut Shadowed Blades Etched Cased Opal Glass



300285WZC Weathered Zinc Finish Weathered White Walnut Blades Etched Cased Opal Glass

Fan Finish

AVI

DBK

Distressed

Black

wzc

Weathered

Zinc

**BLADE SPECS** 

(Reversible)

Walnut

FB300285

AVI

Walnut

Shadowed

FB300285

DBK

Dark

Walnut

FB300285

WZC

Blade Finish & Part Number

(Side 1)

Distressed Antique Gray FB300285

AVI

Walnut

FB300285

DBK

Weathered White Walnut FB300285 WZC

## INCLUDED FEATURES

## Blades (9) Included

- 14° Pitch
- 85" Sweep
- Reversible
- Wood Veneer

Downrods 6" Downrod with 1" (O.D.)

**Downlight** Replaceable. 17W Dimmable Integrated LED Platform, 1,600 Lumens, 3,000K

Downlight Glass Etched Cased Opal

Optional Downlight N/A

Uplight N/A

Uplight Glass N/A

Low Ceiling Adaptable No

Control 6-Speed DC Wall Control System

## FAN FEATURES

Mounting Slope – Pitch 30° or 7/12 Lead Wire 78" cUL Listed Damp Hanging Weight 37.4 lbs. Body Material Steel Warranty www.Kichler.com/Warranty

## MOTOR FEATURES

Motor Size/Type DC-165NL Amps 0.47 on High RPM 76 on High Energy Star<sup>®</sup> No

## INCLUDED CONTROLS

## 6-SPEED DC WALL CONTROL SYSTEM

- 6 Forward Speeds, Reverse & Motor Off
- Lights On/Off with Full-Range Dimming
- No More Than Two Fans on One Circuit
- Faceplates Included in 3 Colors

## OPTIONAL CONTROLS



DC COOLTOUCH<sup>™</sup> TRANSMITTER -FULL FUNCTION 371075 (Shown)

## COORDINATING LIGHTING

To see more from these collections visit Kichler.com.



Sconce 44015WZC



## HANGING MEASUREMENTS

	WITH 6" DOWNROD			
Fixture Drop (from ceiling)	Blade Drop (from ceiling)	Housing (width)	<b>Ceiling Canopy</b> (width)	A B 
<b>A:</b> 16.50"	<b>B:</b> 14.00"	<b>C:</b> 7.00"	<b>D:</b> 6.00"	↓ <u>↓</u>

AIR PERFORMANCE				
AIRFLOW Cubic Ft. Per Minute on High	POWER USAGE Watts on High (Excludes Lights)	AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt		
9294	31	300		





Shown: 300265DBK Distressed Black Finish, Etched Cased Opal Glass, with Walnut Shadowed Blades

# 65" Gentry LED



300265AVI Anvil Iron Finish Distressed Antique Gray Blades Etched Cased Opal Glass



300265WZC Weathered Zinc Finish Dark Walnut Blades Etched Cased Opal Glass

## INCLUDED FEATURES

### Blades (9) Included

- 14° Pitch
- 65" Sweep
- Reversible
- Wood Veneer

Downrods 6" Downrod with 1" (O.D.)

**Downlight** Replaceable. 17W Dimmable Integrated LED Platform, 1,600 Lumens, 3,000K

Downlight Glass Etched Cased Opal

Optional Downlight N/A

Uplight N/A

Uplight Glass N/A

Low Ceiling Adaptable No

Control 6-Speed DC Wall Control System

## FAN FEATURES

Mounting Slope – Pitch 30° or 7/12 Lead Wire 78" cUL Listed Damp Hanging Weight 33.0 lbs. Body Material Steel Warranty www.Kichler.com/Warranty

## MOTOR FEATURES

Motor Size/Type DC-165NL Amps 0.45 on High RPM 122 on High Energy Star® No



## 6-SPEED DC WALL CONTROL SYSTEM

- 6 Forward Speeds, Reverse & Motor Off
- Lights On/Off with Full-Range Dimming
- No More Than Two Fans on One Circuit
- Faceplates Included in 3 Colors

## OPTIONAL CONTROLS



COORDINATING LIGHTING

## To see the complete Fulton Cross™



В

D

## HANGING MEASUREMENTS

	WITH 6" D	OWNROD			•
Fixture Drop (from ceiling)	Blade Drop (from ceiling)	Housing (width)	<b>Ceiling Canopy</b> (width)	A	1
<b>A:</b> 16.50"	<b>B:</b> 14.00"	<b>C:</b> 7.00"	D: 6.00"		

AIR PERFORMANCE				
AIRFLOW Cubic Ft. Per Minute on High	POWER USAGE Watts on High (Excludes Lights)	AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt		
8061	34	237		





