

# $52^{\prime\prime} \;\; \text{Hendrik}^{^{\prime\prime}}$



# **BLADE SPECS**

Fan Finish

Blade Finish & Part Number (Side 1) (Reversible)













### INCLUDED FEATURES

Blades (5) Included

- 14° Pitch
- 52" Sweep
- Reversible
- Wood

**Downrods** 4" and 12" Downrod with 1" (O.D.)

**Downlight** Integrated. Uses (3) E-12 40-W B-10 Lamps

**Downlight Glass** Satin Etched Cased Opal or Light Umber Etched

Optional Downlight N/A

Uplight N/A

Uplight Glass N/A

**Low Ceiling Adaptable** Yes, See our Optional Flush Mount Accessory 337008 on page 310

**Control** 3-Speed CoolTouch<sup>™</sup> - Full Function

### FAN FEATURES

Mounting Slope – Pitch 30° or 7/12

Lead Wire 78"

cUL Listed Indoor

Hanging Weight 25.10 lbs.

Warranty Limited Lifetime

# MOTOR FEATURES

Motor Size/Type 172mm x 17mm, AC

Amps 0.57 on High RPM 154 on High

Energy Star N/A

# INCLUDED CONTROLS

## 3-SPEED COOLTOUCH™ FULL FUNCTION

- 3 Forward Speeds & Reverse
- Lights On/Off with Full Range Dimming
- Motor Off



### OPTIONAL CONTROLS



### 370038MULTR

**WALL TRANSMITTER – FULL FUNCTION** See pages 306-308 for more information.

### COORDINATING LIGHTING

To see the complete  $\mathsf{Hendrik}^\mathsf{m}$  Collection visit kichler.com.




# HANGING MEASUREMENTS

# WITH 4" DOWNROD

Fixture Drop	Blade Drop	Housing	Ceiling Canopy
(from ceiling)	(from ceiling)	(width)	(width)
<b>A:</b> 16.50"	<b>B:</b> 10.50"	<b>C:</b> 12.25"	

# WITH 12" DOWNROD

WITH IZ DOWNROD					
Fixture Drop (from ceiling)	Blade Drop (from ceiling)	Housing (width)	Ceiling Canopy (width)		
<b>A:</b> 24.50"	<b>B:</b> 18.50"	<b>C:</b> 12.25"	<b>D:</b> 5.95"		



# AIR PERFORMANCE

AIRFLOW POWER AIRFLOW USAGE **EFFICIENCY** 5022 70 72 Cubic Ft. Watts on High Cubic Ft. Per Minute (Excludes Per Minute Per Watt on High Lights)