

120V LED/INCANDESCENT ACCENT

IN-GROUND INCANDESCENT – PAR38



AZ

15295 AZ

SMALL IN-GROUND – PAR20/PAR30



AZ

15268 AZ

Ordering Guide & Finish	15295 AZ	15268 AZ
Housing	Durable thermoplastic composite resin. Tempered convex glass lens fully sealed for watertight outdoor use.	Durable thermoplastic composite resin. Tempered convex glass lens fully sealed for watertight outdoor use.
Lamp Base	4000V (4KV) pulse rated medium base porcelain socket. Re-enterable encapsulant	Medium base porcelain socket
Supplied Lamp	Lamp not supplied unless noted	Lamp not supplied unless noted
Incandescent Lamp Options	150-W Max. PAR38 Incandescent	75-W Max. PAR20 or PAR30 and PAR30 Longneck Incandescent
LED Lamp Options	17W PAR38 Wet (18093-18098) see page 166. Compares up to 75W Halogen.	7W PAR20 Wet (18081-18086) see page 169. Compares up to 35W Halogen. 12W PAR30 Wet (18087-18029) see page 169. Compares up to 50W Halogen. 12W PAR30L Wet (18111-18116) see page 169. Compares up to 50W Halogen.
Wiring	Architectural Bronze™	Architectural Bronze™
Aiming	With adjustable aim assembly, 15° angle, 358° rotation with wing-nut locking mechanism	With adjustable aim assembly, 25° angle, 358° rotation
Optional Access.	15608 – Concrete Pour Kit (Drive-over) 15616 WH10 – Gel Encapsulant 10 pack	N/A
Optional Lens Accessories	15626 – Blue Filter with gasket 15688 – Rock Guard	15694 – Rock Guard
Notes	Drive over capacity 3,000 lbs. Adjustable to 15° angle. Use with blue filter 15626 to intensify green color in the landscape.	U.S. Patent No. 5,230,559. Korea Patent No. 126459. For use with PAR20 and PAR30 lamps.