

Hatteras Bay LED 3000K 52" Fan Distressed Black
 310018DBK (Anvil Iron)



Project Name: _____
 Location: _____
 Type: _____
 Qty: _____
 Comments: _____

Airflow

CFM (High)	6124
CFM (Low)	2122
RPM (High)	146
RPM (Low)	56

Certifications/Qualifications

Location Rating	CSA UL Listed Damp www.kichler.com/warranty
-----------------	--

Dimensions

Base Backplate	6.75 DIA
Downrod 1	1.00 OD X 12.00"
Downrod 2 - Measurement A	16.50"
Downrod 2 - Measurement B	12.50"
Downrod 2 - Measurement C	15.25"
Weight	33.00 LBS
Height	22.50"
Width	52.00"

Electrical

Amps (High)	0.69
Amps (Low)	0.28
Motor Size	172MM X 20MM
Motor Type	AC INDUCTION

Mounting/Installation

Minimum Distance from Fan to 7 feet Floor	
Interior/Exterior	Interior
Lead Wire Length	78
Low Ceiling Adaptable	Yes, Dual Mount Included
Mounting Weight	33.00 LBS

Photometrics

Color Rendering Index	80
Kelvin Temperature	3000K

Primary Lamping

Dimmable	Yes
Downlight Included	Yes
Downlight Option	Integrated
Lamp Included	Integrated
Light Source	LED
# of Bulbs/LED Modules	1
Watts (High)	82
Watts (Low)	15

Product/Ordering Information

SKU	310018DBK
Finish	Antique/Burnished
Style	Traditional
UPC	783927600187

Specifications

Blade Finish 1	WALNUT
Blade Finish 2	CHERRY
Blade Material	ABS
Blade Pitch	14
Blades Included	Yes

Blade Sweep	52
Diffuser Description	Fresnel Lens Gloss White Inside-Clear Outside
Material	STEEL, PLYWOOD, GLASS
Max Stem Tilt	22 Degrees
Number of Blades	5
Blades Reversible	Yes
Wall Control Included	Yes

Additional Finishes



Anvil Iron



Anvil Iron



Weathered Zinc

Kichler

7711 East Pleasant Valley Road Cleveland, Ohio 44131-8010
Toll free: 866.558.5706 or kichler.com

Notes:

- 1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
- 2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.

KICHLER®