

# TULLY™

ANTIQUE PEWTER FINISH WITH  
SATIN ETCHED CASED OPAL GLASS



**A** | 45149 AP  
Wall Sconce  
NOT TO SCALE



**B** | 45150 AP



**C** | 45151 AP



**D** | 45152 AP



**E** | 45193 AP

## TULLY™

|          | ITEM # | FINISH | INCAND.<br>BULB | W     | H   | EXT. | HCWO | NOTES  |
|----------|--------|--------|-----------------|-------|-----|------|------|--|
| <b>A</b> | 45149  | AP     | (1) 100W (M)    | 5     | 6.5 | 6.75 | 4    | ⓓ (18-25W CFL) May be installed on wall with glass up or down. |
| <b>B</b> | 45150  | AP     | (2) 100W (M)    | 15    | 6.5 | 6.75 | 4    | ⓓ (18-25W CFL) May be installed on wall with glass up or down. |
| <b>C</b> | 45151  | AP     | (3) 100W (M)    | 24    | 6.5 | 6.75 | 4    | ⓓ (18-25W CFL) May be installed on wall with glass up or down. |
| <b>D</b> | 45152  | AP     | (4) 100W (M)    | 32    | 6.5 | 6.75 | 4    | ⓓ (18-25W CFL) May be installed on wall with glass up or down. |
| <b>E</b> | 45193  | AP     | (5) 100W (M)    | 40.25 | 6.5 | 6.75 | 4    | ⓓ (18-25W CFL) May be installed on wall with glass up or down. |

Measurements shown in inches. U.S. & Canada Patent Pending.

## TULLY™

POLISHED CHROME FINISH WITH  
SATIN ETCHED CASÉD OPAL GLASS



A | 45150 CH



B | 45151 CH



C | 45152 CH



D | 45193 CH



E | 45149 CH  
Wall Sconce  
NOT TO SCALE

## TULLY™

|   | ITEM # | FINISH | INCAND.<br>BULB | W     | H   | EXT. | NOTES  |
|---|--------|--------|-----------------|-------|-----|------|--|
| A | 45150  | CH     | (2) 100W (M)    | 15    | 6.5 | 6.75 | ⓓ (18-25W CFL) May be installed on wall with glass up or down. |
| B | 45151  | CH     | (3) 100W (M)    | 24    | 6.5 | 6.75 | ⓓ (18-25W CFL) May be installed on wall with glass up or down. |
| C | 45152  | CH     | (4) 100W (M)    | 32    | 6.5 | 6.75 | ⓓ (18-25W CFL) May be installed on wall with glass up or down. |
| D | 45193  | CH     | (5) 100W (M)    | 40.25 | 6.5 | 6.75 | ⓓ (18-25W CFL) May be installed on wall with glass up or down. |
| E | 45149  | CH     | (1) 100W (M)    | 5     | 6.5 | 6.75 | ⓓ (18-25W CFL) May be installed on wall with glass up or down. |

Measurements shown in inches. U.S. & Canada Patent Pending.