

$52^{\prime\prime} \text{ Kittery Point}^{\ast\prime}$



BLADE SPECS

Fan Finish

Blade Finish & Part Number (Side 1) (Reversible)













PN Polished Nickel





INCLUDED FEATURES

Blades (5) Included

- 14° Pitch
- 52" Sweep
- Reversible
- Wood

Downrods 6" and 12" Downrod with 1" (O.D.)

Downlight Integrated. Uses (4) E-12 40-W Krypton/T3 Lamps

Downlight Glass Etched White

Optional Downlight N/A

Uplight N/A

Uplight Glass N/A

Low Ceiling Adaptable Yes, see our Optional Flush Mount Accessory 337008 on page 310

Control 3-Speed CoolTouch[™] - Full Function

FAN FEATURES

Mounting Slope – Pitch 30° or 7/12

Lead Wire 78"

cUL Listed Indoor

Hanging Weight 31.60 lbs.

Warranty Limited Lifetime

MOTOR FEATURES

Motor Size/Type 188mm x 15mm, AC

Amps 0.49 on High

RPM 166 on High

Energy Star N/A

INCLUDED CONTROLS

3-SPEED COOLTOUCH™ FULL FUNCTION

- 3 Forward Speeds & Reverse
- Lights On/Off with Full Range Dimming
- Motor Off



OPTIONAL CONTROLS



370038MULTR

WALL TRANSMITTER – FULL FUNCTION

See pages 306-308 for more information.

COORDINATING LIGHTING

To see the complete Kittery Point $^{\text{\tiny{M}}}$ Collection visit kichler.com.




HANGING MEASUREMENTS

WITH 6" DOWNROD

Fixture Drop	Blade Drop	Housing	Ceiling Canopy
(from ceiling)	(from ceiling)	(width)	(width)
A: 18.25"	B: 11.75"	C: 16.25"	D: 6.10"

WITH 12" DOWNROD

WITH E BOWNROD					
Fixture Drop (from ceiling)	Blade Drop (from ceiling)	Housing (width)	Ceiling Canopy (width)		
A: 24.25"	B: 17.75"	C: 16.25"	D: 6.10"		



AIR PERFORMANCE

AIRFLOW	POWER USAGE	AIRFLOW EFFICIENCY
5054	59	86
Cubic Ft.	Watts on High	Cubic Ft.
Per Minute	(Excludes	Per Minute
on High	Lights)	Per Watt