

120V 29W LED ACCENT



16204 AZT, BBR, WHT

16205 AZT, BBR, WHT

16208 AZT, BBR, WHT

Beam Spread	Beam Spread 10° Spot		Beam Spread 35° Flood		Beam Spread 60° Wide Flood	
Kelvin	3000K – Pure White	4250K – Cool White	3000K – Pure White	4250K – Cool White	3000K – Pure White	4250K – Cool White
Ordering Guide & Finish	16204 AZT30 16204 BBR30 16204 WHT30	16204 AZT42 16204 BBR42 16204 WHT42	16205 AZT30 16205 BBR30 16205 WHT30	16205 AZT42 16205 BBR42 16205 WHT42	16208 AZT30 16208 BBR30 16208 WHT30	16208 AZT42 16208 BBR42 16208 WHT42
Watts/Lumens	Compares to Halogen 100W PAR38 or greater					
Housing	Cast Aluminum, Cast Brass					
Light Source	8 Integrated High Output Cree® LEDs, tightly binned for color uniformity					
Color Temp. (CCT) & CRI	3000K (-45/+130) Pure White 3000K = 80s			4250K (-250/+250) Cool White 4250K = 85 minimum		
Optics	Radiax™ Reflector					
Power Usage	29W, .27VA, .90pf					
Operating Voltage Range	108-132V AC, 50-60 Hz					
Lumen Maint.	Tested to an L-70 of 40,000 hours					
Total Lumens & Efficacy	3000K = 1,131 Lm 3000K = 39 Lm/W		4250K = 1,368 Lm 4250K = 47 Lm/W			
Wiring	8" of usable 200° C 18AWG wire leads					
Mounting Access. (Included)	N/A					
Optional Accessories	15276 – Power Post® 15601 – Surface Mounting Flange, for attachment to junction box 15609 – Junction Box Mounting Bracket					
Notes	Subjected to Highly Accelerated Life Testing – 3rd party reliability testing. Not for use with electronic transformers. *Cree is a registered trademark of Cree, Inc. Brass will naturally patina over time.					