

## 12V LED ACCENT

### 12V 13W LED ACCENT



**16009 AZT, BBR, BKT**

**16010 AZT, BBR, BKT, WHT**

**16011 AZT, BBR, BKT**

Beam Spread	Beam Spread 10° Spot		Beam Spread 35° Flood		Beam Spread 60° Wide Flood	
Kelvin	2700K – Warm White	3000K – Pure White	2700K – Warm White	3000K – Pure White	2700K – Warm White	3000K – Pure White
Ordering Guide & Finish	16009 AZT27 16009 BBR27 16009 BKT27	16009 AZT30 16009 BBR30 16009 BKT30	16010 AZT27 16010 BBR27 16010 BKT27 16010 WHT27	16010 AZT30 16010 BBR30 16010 BKT30 16010 WHT30	16011 AZT27 16011 BBR27 16011 BKT27	16011 AZT30 16011 BBR30 16011 BKT30
Watts/Lumens	Compares to Halogen 75W MR16					
Housing	Cast Aluminum, Cast Brass					
Light Source	5 Integrated High Output Cree® LEDs, tightly binned for color uniformity, and constant current driver					
Color Temp. (CCT) & CRI	2700K (-50/+100) Warm White 3000K (-45/+130) Pure White / 80s CRI					
Optics	Radiax™ Reflector					
Power Usage at 12V AC Input VA and Watts	13W, 18.5VA					
Operating Voltage Range	9V-15V AC/DC with no loss in output due to constant current technology					
Lumen Maint.	Tested to an L-70 of 40,000 hours					
Delivered Lumens & Efficacy	2700K = 520 Lm 2700K = 40 Lm/W		3000K = 590 Lm 3000K = 45 Lm/W			
Wiring	24" of usable #18-2, SPT-1W leads. Wire connectors supplied. Includes LVPC installed. See page 134.					
Mounting Access. (Included)	8" slotted in-ground stake					
Optional Accessories	15601 – Surface Mounting Flange 15609 – Junction Box Mounting Bracket 15645, 15656, 15657, 15658 or 15570 – Stems		15607 – Surface Bracket 15647 – 90° Elbow			
Notes	Textured white only available in 35° beam. Brass will naturally patina over time. *Cree is a registered trademark of Cree, Inc.					