

12V 21W LED ACCENT



**16012 AZT, BBR, BKT**

**16013 AZT, BBR, BKT, WHT**

**16014 AZT, BBR, BKT**

Beam Spread	Beam Spread 10° Spot		Beam Spread 35° Flood		Beam Spread 60° Wide Flood	
Kelvin	2700K – Warm White	3000K – Pure White	2700K – Warm White	3000K – Pure White	2700K – Warm White	3000K – Pure White
Ordering Guide & Finish	16012 AZT27 16012 BBR27 16012 BKT27	16012 AZT30 16012 BBR30 16012 BKT30	16013 AZT27 16013 BBR27 16013 BKT27 16013 WHT27	16013 AZT30 16013 BBR30 16013 BKT30 16013 WHT30	16014 AZT27 16014 BBR27 16014 BKT27	16014 AZT30 16014 BBR30 16014 BKT30
Watts/Lumens	Compares to Halogen 75W MR16					
Housing	Cast Aluminum, Cast Brass					
Light Source	8 Integrated High Output Cree® LEDs, tightly binned for color uniformity, and constant current driver					
Color Temp. (CCT) & CRI	2700K (-50/+100) Warm White 3000K (-45/+130) Pure White / 80s CRI					
Optics	Radiax™ Reflector					
Power Usage at 12V AC Input VA and Watts	21W, 27.0VA					
Operating Voltage Range	9V-15V AC/DC with no loss in output due to constant current technology					
Lumen Maint.	Tested to an L-70 of 40,000 hours					
Delivered Lumens & Efficacy	2700K = 947 Lm 2700K = 45 Lm/W		3000K = 993 Lm 3000K = 47 Lm/W			
Wiring	24" of usable #18-2, SPT-1W leads. Wire connectors supplied. Includes LVPC installed. See page 134.					
Mounting Access. (Included)	8" slotted in-ground stake					
Optional Accessories	15601 – Surface Mounting Flange    15609 – Junction Box Mounting Bracket 15607 – Surface Bracket            15647 – 90° Elbow 15645, 15656, 15657, 15658 or 15570 – Stems					
Notes	Textured white only available in 35° beam. Brass will naturally patina over time. *Cree is a registered trademark of Cree, Inc.					