

12V LED ACCENT

12V 4W LED ACCENT



16003 AZT, BBR, BKT

16004 AZT, BBR, BKT, WHT

16005 AZT, BBR, BKT

Beam Spread	Beam Spread 10° Spot		Beam Spread 35° Flood		Beam Spread 60° Wide Flood	
Kelvin	2700K – Warm White	3000K – Pure White	2700K – Warm White	3000K – Pure White	2700K – Warm White	3000K – Pure White
Ordering Guide & Finish	16003 AZT27 16003 BBR27 16003 BKT27	16003 AZT30 16003 BBR30 16003 BKT30	16004 AZT27 16004 BBR27 16004 BKT27 16004 WHT27	16004 AZT30 16004 BBR30 16004 BKT30 16004 WHT30	16005 AZT27 16005 BBR27 16005 BKT27	16005 AZT30 16005 BBR30 16005 BKT30
Watts/Lumens	Compares to 20W Halogen MR16					
Housing	Cast Aluminum, Cast Brass					
Light Source	1 Integrated High Output Cree® LED, tightly binned for color uniformity, and constant current driver					
Color Temp. (CCT) & CRI	2700K (-50/+100) Warm White 3000K (-45/+130) Pure White / 80s CRI					
Optics	Radiax™ Reflector					
Power Usage at 12V AC Input VA and Watts	4W, 5.5VA					
Operating Voltage Range	9V-15V AC/DC with no loss in output due to constant current technology					
Lumen Maint.	Tested to an L-70 of 40,000 hours					
Delivered Lumens & Efficacy	2700K = 151 Lm 2700K = 38 Lm/W		3000K = 180 Lm 3000K = 45 Lm/W			
Wiring	24" of usable #18-2, SPT-1W leads. Wire connectors supplied. Includes LVPC installed. See page 134.					
Mounting Access. (Included)	8" slotted in-ground stake					
Optional Accessories	15601 – Surface Mounting Flange 15609 – Junction Box Mounting Bracket 15607 – Surface Bracket 15647 – 90° Elbow 15645, 15656, 15657, 15658 or 15570 – Stems					
Notes	Textured white only available in 35° beam. Brass will naturally patina over time. *Cree is a registered trademark of Cree, Inc.					