

KICHLER


Landscape Path & Spread



PROJECT:
TYPE:
ORDERING # :
COMMENTS:


FEATURES

- Cast Aluminum Housing, w/ Textured Black or Architectural Bronze Finish
- High Impact Resistant Diffuser - Mounting Stems & Bollard Kits Sold Separately
- 30" of Usable 105° 18 AWG Wire Leads
- 120V Medium Base Porcelain Socket w/ Nickel Plated Screw Shell
- Maximum 75W A-19 Incandescent Lamp (Not Included)
- ANSI / UL Listed Wet Location
- Housing Includes a 1-Year Warranty From Date of Purchase



ORDERING INFORMATION

EXAMPLE: 15211 AZT (Product # & Finish)

PRODUCT	FINISH	STEM SPECS/OPTIONS	BOLLARD SPECS/OPTIONS	OPTIONS/ACCESSORIES																																							
15211	AZT - Textured Architectural Bronze 	<p>Made of Corrosion Resistant Aluminum Alloy w/ Baked Thermoset Powder Coat Finish to Match Fixtures - All Stems are .75" in Overall Diameter - Used With In-Ground Support Stakes (For Low Voltage Applications Only) Or Used With Surface Mounting Flange (Low or Line Voltage Applications)</p> <p>15645AZT - Bronze Finish .50 NPSM thd. x 6" in Length 15645BKT - Black Finish .50 NPSM thd. x 6" in Length</p> <p>15656AZT - Bronze Finish .50 NPSM thd. x 12" in Length 15656BKT - Black Finish .50 NPSM thd. x 12" in Length</p> <p>15657AZT - Bronze Finish .50 NPSM thd. x 18" in Length 15657BKT - Black Finish .50 NPSM thd. x 18" in Length</p> <p>15658AZT - Bronze Finish .50 NPSM thd. x 24" in Length 15658BKT - Black Finish .50 NPSM thd. x 24" in Length</p> 	<p>Cast Aluminum Internal Mounting Plate, Including Lag Bolts For Deck or Surface Mounting. Extruded Aluminum Bollard w/ Baked Thermoset Powder Coat Finish - All Bollard Mounting Stems Are 4.0625" Overall Diameter</p> <p>15665AZT - Bronze Finish 4.0625" ID x 18" in Length 15665BKT - Black Finish 4.0625" ID x 18" in Length</p> <p>15666AZT - Bronze Finish 4.0625" ID x 24" in Length 15666BKT - Black Finish 4.0625" ID x 24" in Length</p> <p>15667AZT - Bronze Finish 4.0625" ID x 36" in Length 15667BKT - Black Finish 4.0625" ID x 36" in Length</p> 	<p>Mounting Accessories</p> <p>15276BK - <u>Power Post</u>: A Fast, One-Step Connector - Made of Impact / Corrosion Resistant PVC - 2.250" Inside Diameter to Accomodate Conduits of Different Sizes - Accepts .50 NPSM Thread - Designed For 120V Line Voltage Landscape Lighting, Eliminating Need For Above or Below Ground Boxes. - Built-in Stabilizer Removes Need For Concrete </p> <p>15578BK - Bollard Mounting Stake - Use With 12V & 120V Fixture Bollard Mounting Kits As Allowed By Local Electrical Codes - Made of Corrosion Resistant Extruded PVC - 23" Length Has Increased Support & Stability - Fitting Provided to Mount Bollard in Soil </p> <p>15671ST - 4" Bollard Template Kit - For Permanent Installation in Concrete The Kits Include a Positioning Template, Anchor Bolts, and Mounting Hardware </p> <p>15601AZT - Cast Aluminum Surface Mounting Flange w/ Bronze Finish, Neoprene Gasket For Watertight Seal 15601BKT - Cast Aluminum Surface Mounting Flange w/ Black Finish, Neoprene Gasket For Watertight Seal </p> <p>15602AL - Anodized Aluminum Nipple - For Attaching Fixture Directly to The 15601 Flange </p>																																							
	BKT - Textured Black 																																										
<p>Footcandles/Distance from Fixture Center 15211 (120V) 75W A19 light bulb</p> <table border="1"> <thead> <tr> <th>Mounting Height</th> <th>1'</th> <th>2'</th> <th>3'</th> <th>4'</th> <th>5'</th> <th>6'</th> <th>7'</th> <th>8'</th> <th>9'</th> </tr> </thead> <tbody> <tr> <td>12"</td> <td>27.1</td> <td>11.7</td> <td>2.8</td> <td>1.2</td> <td>.89</td> <td>.34</td> <td>.18</td> <td>.07</td> <td>-</td> </tr> <tr> <td>18"</td> <td>19</td> <td>9.5</td> <td>4.6</td> <td>1.7</td> <td>.82</td> <td>.45</td> <td>.31</td> <td>.18</td> <td>.07</td> </tr> <tr> <td>24"</td> <td>14.6</td> <td>7.8</td> <td>4.8</td> <td>2.4</td> <td>1</td> <td>.55</td> <td>.27</td> <td>.27</td> <td>.14</td> </tr> </tbody> </table>		Mounting Height	1'	2'	3'	4'	5'	6'	7'	8'	9'	12"	27.1	11.7	2.8	1.2	.89	.34	.18	.07	-	18"	19	9.5	4.6	1.7	.82	.45	.31	.18	.07	24"	14.6	7.8	4.8	2.4	1	.55	.27	.27	.14		
Mounting Height	1'	2'	3'	4'	5'	6'	7'	8'	9'																																		
12"	27.1	11.7	2.8	1.2	.89	.34	.18	.07	-																																		
18"	19	9.5	4.6	1.7	.82	.45	.31	.18	.07																																		
24"	14.6	7.8	4.8	2.4	1	.55	.27	.27	.14																																		

NOTES

For Warranty Information, please visit www.landscapelighting.com

We reserve the right to revise the design or components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.

