CROSS CREEK LANTERN 7. 27"	75"	ECLIPSE™ 9" 25" BKT TZT	26.25"
	15232 AGZ	15236 BKT, TZT	15239 OZ
Ordering Guide & Finish	15232 AGZ	15236 BKT, TZT	15239 OZ
Housing	Aluminum with textured linen seedy glass side panels and clear glass bottom panel	Cast Aluminum with clear glass	Brass
Lamp Туре	Up to 25W Max. A19 light bulb (not supplied)	Up to 25W Max. A19 light bulb (not supplied)	Up to 25W Max. A19 light bulb (not supplied)
Wiring	6" of usable 105°C, 18 AWG wire leads. 120V medium base porcelain socket.	6" of usable 105° C 18 AWG wire leads. 120V medium base porcelain socket with nickel plated screw shell.	6" of usable 105° C 18 AWG wire leads. 120V medium base porcelain socket with nickel plated screw shell.
Optional Accessories	15276 – Power Post® 15601 – Surface Mounting Flange (for attachment to junction box, not included)	15276 – Power Post® 15601 – Surface Mounting Flange (for attachment to junction box, not included)	15276 – Power Post® 15601 – Surface Mounting Flange (for attachment to junction box, not included)
Notes	U.S. Patent No. D580,084	U.S. Patent No. D580,084	U.S. Patent No. D580,084
Fixture Photometric (fc)	Distance 1' 2' 3' 4' 5' 6' 7' 8' 9' from Light 1' 2' 3' 4' 5' 6' 7' 8' 9' Foot 2.8 1.9 .4 .1	Distance from Light 1' 2' 3' 4' 5' 6' 7' 8' 9' Foot Candles 3 11.5 3.9 1.5 .70 .30 .1	Distance from Light 1' 2' 3' 4' 5' 6' 7' 8' 9'   Foot Candles 76 31 10.2 3.6 1.6 .7 .3 .2 .1