LARGE ECLIPSE™ 25"		ECLIPSE™
	15336 BKT, TZT	15323 AZT, BKT, TZT
Ordering Guide & Finish	15336 BKT 15336 TZT	15323 AZT 15323 BKT 15323 TZT
Housing	Cast Aluminum with clear glass	Cast Aluminum
Lamp Base	12V S8 wedge base socket	12V S8 wedge base socket
Supplied Lamp	24.4-W(VA) 3156K (15598 CLR) Krypton light source Power usage at 12V AC input VA MAX: 24.4-W(VA)	24.4-W(VA) 3156K (15598 CLR) Krypton light source Power usage at 12V AC input VA MAX: 24.4-W(VA)
Incandescent Lamp Options	18.5-W(VA) 3155K (15599 CLR)	18.5-W(VA) 3155K (15599 CLR)
LED Lamp Options	2W (18036-18038) see page 137. Compares up to 18.5W Krypton.	2W (18036-18038) see page 137. Compares up to 18.5W Krypton.
Wiring	35" of usable #18-2, SPT-1-W leads. Cable connectors supplied.	34" of usable #18-2, SPT-1-W leads. Cable connectors supplied.
Mounting Access. (Included)	NA	8" In-ground slotted stake and 18" stem
Optional Accessories	15601 – Surface Mounting Flange 15607– Surface Mounting Bracket	15601 – Surface Mounting Flange 15607 – Surface Mounting Bracket
Photometric with Supplied Lamp	Distance from Light 1' 2' 3' 4' 5' 6' 7' 8' 9' Foot Candles 8.7 3.3 1.1 .4 .1 - - - - -	Distance from Light 1' 2' 3' 4' 5' 6' 7' 8' 9' Foot Candles 14.7 4.8 1.8 1 -<