

INCANDESCENT / LED 12V HYBRID PATH & SPREAD



15360 AZT - SIMPLICITY SIDE MOUNT

15333 TZT - CONTOURS

Description	Simple, uncomplicated design for perfect illumination along paths without troublesome glare.	A fresh interpretation of contemporary style. Equally effective as a path light or to highlight a flower bed.																																								
Ordering Guide & Finish	15360 AZT - Textured Architectural Bronze	15333 TZT - Textured Tannery Bronze																																								
Housing	Aluminum	Aluminum																																								
Lamp Base	12V S8 wedge base socket	12V S8 wedge base socket																																								
Supplied Lamp	24.4-W(VA) 3156K (15598 CLR) Krypton light source Power usage at 12V AC input VA MAX: 24.4-W(VA)	24.4-W(VA) 3156K (15598 CLR) Krypton light source Power usage at 12V AC input VA MAX: 24.4-W(VA)																																								
Incandescent Lamp Options	18.5-W(VA) 3155K (15599 CLR)	18.5-W(VA) 3155K (15599 CLR)																																								
LED Lamp Options	2W (18036-18038) see page 159 Compares up to 18.5W Krypton	2W (18036-18038) see page 159 Compares up to 18.5W Krypton																																								
Wiring	35" of usable #18-2, SPT-1-W leads. Cable connector supplied	34" of usable #18-2, SPT-1-W leads. Cable connector supplied																																								
Mounting Acces. Included	8" In-ground stake	8" In-ground stake																																								
Optional Acces.	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket																																								
Notes	N/A	U.S. Patent Pending																																								
Photometric with Supplied Lamp	<table border="1"> <tr> <td>Distance from Light</td> <td>.5'</td> <td>1'</td> <td>2'</td> <td>3'</td> <td>4'</td> <td>5'</td> <td>6'</td> <td>7'</td> <td>8'</td> </tr> <tr> <td>Footcandles</td> <td>20.7</td> <td>10.6</td> <td>3.5</td> <td>1.1</td> <td>.4</td> <td>.1</td> <td>-</td> <td>-</td> <td>-</td> </tr> </table>	Distance from Light	.5'	1'	2'	3'	4'	5'	6'	7'	8'	Footcandles	20.7	10.6	3.5	1.1	.4	.1	-	-	-	<table border="1"> <tr> <td>Distance from Light</td> <td>1'</td> <td>2'</td> <td>3'</td> <td>4'</td> <td>5'</td> <td>6'</td> <td>7'</td> <td>8'</td> <td>9'</td> </tr> <tr> <td>Footcandles</td> <td>11.9</td> <td>6.6</td> <td>2.58</td> <td>.88</td> <td>.28</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </table>	Distance from Light	1'	2'	3'	4'	5'	6'	7'	8'	9'	Footcandles	11.9	6.6	2.58	.88	.28	-	-	-	-
Distance from Light	.5'	1'	2'	3'	4'	5'	6'	7'	8'																																	
Footcandles	20.7	10.6	3.5	1.1	.4	.1	-	-	-																																	
Distance from Light	1'	2'	3'	4'	5'	6'	7'	8'	9'																																	
Footcandles	11.9	6.6	2.58	.88	.28	-	-	-	-																																	

Denotes fixture is compatible with incandescent or LED lamps.