

INCANDESCENT / LED 12V HYBRID PATH & SPREAD



15005 AZT, BKT - FUNDAMENTALS™

15315 AZT, AZT6, BE, BKT - SIDE MOUNT

<b>Description</b>	Louvers direct tiers of light downward for well-shielded, dramatic lighting. Blends nicely with shrubs or flowers along a pathway. Available in stem or deck mount or as a bollard. Mounting stems and bollard kits sold separately. Coordinates with matching deck light 15065 on page 109.	A popular design in a side-mount fixture for more directional lighting without glare. Coordinates with matching deck light 15065 on page 109.																																																																																
<b>Ordering Guide &amp; Finish</b>	15005 AZT - Textured Architectural Bronze 15005 BKT - Textured Black	15315 AZT - Textured Architectural Bronze 15315 AZT6 - Same as 15315 AZT. Bulk packed in 6 (unbreakable master) 15315 BKT - Textured Black																																																																																
<b>Housing</b>	Cast Aluminum with molded ribbed diffuser of clear UV stabilized high impact resistant polycarbonate	Cast Aluminum																																																																																
<b>Lamp Base</b>	12V S8 wedge base socket	12V S8 wedge base socket																																																																																
<b>Supplied Lamp</b>	24.4-W(VA) 3156K (15598 CLR) Krypton light source Power usage at 12V AC input VA MAX: 24.4-W(VA)	24.4-W(VA) 3156K (15598 CLR) Krypton light source Power usage at 12V AC input VA MAX: 24.4-W(VA)																																																																																
<b>Incandescent Lamp Options</b>	18.5-W(VA) 3155K (15599 CLR)	18.5-W(VA) 3155K (15599 CLR)																																																																																
<b>LED Lamp Options</b>	2W (18036-18038) see page 159 Compares up to 18.5W Krypton	2W (18036-18038) see page 159 Compares up to 18.5W Krypton																																																																																
<b>Wiring</b>	52" of usable #18-2, SPT-1-W leads. Cable connector supplied	35" of usable #18-2, SPT-1-W leads. Cable connector supplied																																																																																
<b>Mounting Acces. Included</b>	NA	8" In-ground stake and 18" stem																																																																																
<b>Optional Acces.</b>	15656, 15657, 15658 or 15570 - Stems 15575 BK, 15576 BK or 15578 - Stakes 15665, 15666 or 15667 - Bollard 15671 ST - Bollard Template Kit 15601 - Surface Mounting Flange 15602 - Flange Mounting Nipple 15607 - Surface Mounting Bracket	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket																																																																																
<b>Integrated LED Option</b>	NA	15815 - on Page 15																																																																																
<b>Photometric with Supplied Lamp</b>	<table border="1"> <thead> <tr> <th>Stem Height</th> <th>1'</th> <th>2'</th> <th>3'</th> <th>4'</th> <th>5'</th> <th>6'</th> <th>7'</th> <th>8'</th> <th>9'</th> </tr> </thead> <tbody> <tr> <td>12"</td> <td>2.1</td> <td>.93</td> <td>.67</td> <td>.18</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>18"</td> <td>1.8</td> <td>.73</td> <td>.4</td> <td>.27</td> <td>0.3</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>24"</td> <td>1.2</td> <td>.67</td> <td>.33</td> <td>.35</td> <td>.27</td> <td>.15</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Stem Height	1'	2'	3'	4'	5'	6'	7'	8'	9'	12"	2.1	.93	.67	.18	-	-	-	-	-	18"	1.8	.73	.4	.27	0.3	-	-	-	-	24"	1.2	.67	.33	.35	.27	.15	-	-	-	<table border="1"> <thead> <tr> <th>Stem Height</th> <th>1'</th> <th>2'</th> <th>3'</th> <th>4'</th> <th>5'</th> <th>6'</th> <th>7'</th> <th>8'</th> <th>9'</th> </tr> </thead> <tbody> <tr> <td>12"</td> <td>18.7</td> <td>4.3</td> <td>1.4</td> <td>.27</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>18" (as supplied)</td> <td>15</td> <td>5.2</td> <td>1.8</td> <td>.8</td> <td>.27</td> <td>.03</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>24"</td> <td>11.6</td> <td>5.1</td> <td>2.2</td> <td>.97</td> <td>.48</td> <td>.2</td> <td>.07</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Stem Height	1'	2'	3'	4'	5'	6'	7'	8'	9'	12"	18.7	4.3	1.4	.27	-	-	-	-	-	18" (as supplied)	15	5.2	1.8	.8	.27	.03	-	-	-	24"	11.6	5.1	2.2	.97	.48	.2	.07	-	-
Stem Height	1'	2'	3'	4'	5'	6'	7'	8'	9'																																																																									
12"	2.1	.93	.67	.18	-	-	-	-	-																																																																									
18"	1.8	.73	.4	.27	0.3	-	-	-	-																																																																									
24"	1.2	.67	.33	.35	.27	.15	-	-	-																																																																									
Stem Height	1'	2'	3'	4'	5'	6'	7'	8'	9'																																																																									
12"	18.7	4.3	1.4	.27	-	-	-	-	-																																																																									
18" (as supplied)	15	5.2	1.8	.8	.27	.03	-	-	-																																																																									
24"	11.6	5.1	2.2	.97	.48	.2	.07	-	-																																																																									

Denotes fixture is compatible with incandescent or LED lamps.