

INCANDESCENT / LED 12V HYBRID PATH & SPREAD



	<b>15401 AZT - THATCHED ROOF</b>	<b>15443 CO, OB, OB12, TZT, VG - DECORATIVE HAMMERED ROOF</b>																																								
<b>Description</b>	The casual style indicative of island life is reproduced in this cast aluminum lighting fixture. Coordinates with matching deck light 15461 on page 105.	Pierced shade sheds decorative patterned light over shrubs or gardens.																																								
<b>Ordering Guide &amp; Finish</b>	15401 AZT - Textured Architectural Bronze	15443 CO - Unfinished Copper, Copper 15443 OB - Olde Brick®, Brass 15443 OB12 - Same as 15443OB. Bulk packed in 12 (unbreakable master) 15443 TZT - Textured Tannery Bronze™, Brass 15443 VG - Verdigris, Brass																																								
<b>Housing</b>	Cast Aluminum with clear glass sprinkler shield	Brass or Copper (Copper will naturally patina over time)																																								
<b>Lamp Base</b>	12V T3 bi-pin, high temperature porcelain socket	12V S8 wedge base socket																																								
<b>Supplied Lamp</b>	20-W(VA) T3 (17012) Halogen light source Power usage at 12V AC input VA MAX: 20-W(VA)	24.4-W(VA) 3156K (15598 CLR) Krypton light source Power usage at 12V AC input VA MAX: 24.4-W(VA)																																								
<b>Incandescent Lamp Options</b>	10-W(VA) T-3 (17011)	18.5-W(VA) 3155K (15599 CLR)																																								
<b>LED Lamp Options</b>	2W (18042-18044) see page 159 Compares up to 20W Halogen	2W (18036-18038) see page 159 Compares up to 18.5W Krypton																																								
<b>Wiring</b>	20" of usable #18-2, SPT-1-W leads. Cable connector supplied	35" of usable #18-2, SPT-1-W leads. Cable connector supplied																																								
<b>Mounting Acces. Included</b>	8" In-ground stake (Included)	8" In-ground stake (Included)																																								
<b>Optional Acces.</b>	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket																																								
<b>Integrated LED Options</b>	N/A	15843 on page 10.																																								
<b>Notes</b>	N/A	U.S. Patent No. D408,573																																								
<b>Photometric with Supplied Lamp</b>	<table border="1"> <tr> <td>Distance from Light</td> <td>0'</td> <td>1'</td> <td>2'</td> <td>3'</td> <td>4'</td> <td>5'</td> <td>6'</td> <td>7'</td> <td>8'</td> </tr> <tr> <td>Footcandles</td> <td>9.9</td> <td>7.3</td> <td>1.7</td> <td>.76</td> <td>.16</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </table>	Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'	Footcandles	9.9	7.3	1.7	.76	.16	-	-	-	-	<table border="1"> <tr> <td>Distance from Light</td> <td>1'</td> <td>2'</td> <td>3'</td> <td>4'</td> <td>5'</td> <td>6'</td> <td>7'</td> <td>8'</td> <td>9'</td> </tr> <tr> <td>Footcandles</td> <td>8.9</td> <td>2.8</td> <td>.6</td> <td>.15</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </table>	Distance from Light	1'	2'	3'	4'	5'	6'	7'	8'	9'	Footcandles	8.9	2.8	.6	.15	-	-	-	-	-
Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'																																	
Footcandles	9.9	7.3	1.7	.76	.16	-	-	-	-																																	
Distance from Light	1'	2'	3'	4'	5'	6'	7'	8'	9'																																	
Footcandles	8.9	2.8	.6	.15	-	-	-	-	-																																	

Denotes fixture is compatible with incandescent or LED lamps.