

INCANDESCENT / LED 12V HYBRID PATH & SPREAD



	15422 AGZ - COTSWOLD™	15420 AGZ - COTSWOLD™																																								
Description	Curvy edition with old world charm, this path light spreads light with style that blends into nature for a lower profile light source.	Lantern style path light with an old world, curvy cap. A curly stem adds unique charm to a popular traditional look.																																								
Ordering Guide & Finish	15422 AGZ - Aged Bronze	15420 AGZ - Aged Bronze																																								
Housing	Cast Aluminum	Cast Aluminum with weathered white glass																																								
Lamp Base	12V T5 wedge base socket	12V T5 wedge base socket																																								
Supplied Lamp	11.6-W(VA) 912X (17023) Xenon light source Power usage at 12V AC input VA MAX: 16.25-W(VA)	11.6-W(VA) 912X (17023) Xenon light source Power usage at 12V AC input VA MAX: 16.25-W(VA)																																								
Incandescent Lamp Options	16.25-W(VA) 921X (17025) 6.5-W(VA) 918X (17022) 4-W(VA) 901X (17021)	16.25-W(VA) 921X (17025) 6.5-W(VA) 918X (17022) 4-W(VA) 901X (17021)																																								
LED Lamp Options	2W (18039-18041) see page 159 Compares up to 16W Xenon	2W (18039-18041) see page 159 Compares up to 16W Xenon																																								
Wiring	26" of usable #18-2, SPT-1-W leads. Cable connector supplied	28" of usable #18-2, SPT-1-W leads. Cable connector supplied																																								
Mounting Acces. Included	8" In-ground stake	8" In-ground stake																																								
Optional Acces.	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket																																								
Photometric with Supplied Lamp	<table border="1"> <tr> <td>Distance from Light</td> <td>0'</td><td>1'</td><td>2'</td><td>3'</td><td>4'</td><td>5'</td><td>6'</td><td>7'</td><td>8'</td> </tr> <tr> <td>Footcandles</td> <td>8.8</td><td>7</td><td>3.6</td><td>1.4</td><td>.4</td><td>-</td><td>-</td><td>-</td><td>-</td> </tr> </table>	Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'	Footcandles	8.8	7	3.6	1.4	.4	-	-	-	-	<table border="1"> <tr> <td>Distance from Light</td> <td>0'</td><td>1'</td><td>2'</td><td>3'</td><td>4'</td><td>5'</td><td>6'</td><td>7'</td><td>8'</td> </tr> <tr> <td>Footcandles</td> <td>14.9</td><td>2.5</td><td>1.3</td><td>.5</td><td>.1</td><td>-</td><td>-</td><td>-</td><td>-</td> </tr> </table>	Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'	Footcandles	14.9	2.5	1.3	.5	.1	-	-	-	-
Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'																																	
Footcandles	8.8	7	3.6	1.4	.4	-	-	-	-																																	
Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'																																	
Footcandles	14.9	2.5	1.3	.5	.1	-	-	-	-																																	

Denotes fixture is compatible with incandescent or LED lamps.