




INCANDESCENT / LED 12V HYBRID PATH & SPREAD



	15429 TZT - CATHEDRAL™	15457 AZT - PIERCED DOME
<b>Description</b>	Transitional styling with draped arches of interwoven bands.	A cast dome sculpted with a floral band and pierced to reveal a trickle of light.
<b>Ordering Guide &amp; Finish</b>	15429 TZT - Textured Tannery Bronze™	15457 AZT -Textured Architectural Bronze™
<b>Housing</b>	Aluminum	Cast Aluminum
<b>Lamp Base</b>	12V T5 wedge base socket 	12V T5 wedge base socket 
<b>Supplied Lamp</b>	11.6-W(VA) 912X (17023) Xenon light source Power usage at 12V AC input VA MAX: 16.25-W(VA)	16.25-W(VA) 921X (17025) Xenon light source Power usage at 12V AC input VA MAX: 16.25-W(VA)
<b>Incandescent Lamp Options</b>	16.25-W(VA) 921X (17025) 6.5-W(VA) 918X (17022) 4-W(VA) 901X (17021)	11.6-W(VA) 912X (17023) 6.5-W(VA) 918X (17022) 4-W(VA) 901X (17021)
<b>LED Lamp Options</b>	2W (18039-18041) see page 159 Compares up to 16W Xenon	2W (18039-18041) see page 159 Compares up to 16W Xenon
<b>Wiring</b>	24" of usable #18-2, SPT-1-W leads. Cable connector supplied	24" of usable #18-2, SPT-1-W leads. Cable connector supplied
<b>Mounting Acces. Included</b>	8" In-ground stake (Included)	8" In-ground stake (Included)
<b>Optional Acces.</b>	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket
<b>Photometric with Supplied Lamp</b>	Distance from Light 0' 1' 2' 3' 4' 5' 6' 7' 8'	Distance from Light 0' 1' 2' 3' 4' 5' 6' 7' 8'
	Footcandles 7.52 5.42 0.47 1.15 0.32 0.05 - - -	Footcandles 9.36 5.22 3.76 2.02 0.89 0.12 0.05 - -

 Denotes fixture is compatible with incandescent or LED lamps.