

INCANDESCENT / LED 12V HYBRID PATH & SPREAD



**15369 TZT - VINTAGE PARK™**      **15393 OZ - KENTUCKY**      **15426 BKT - ALMERIA™**

<b>Description</b>	Graceful curves and elegant detailing in a vintage design.	Classic path light tastefully captures the traditional hunt club style.	Graceful curves and elegant detail are silhouetted by a tawny glow for a classic elegant look emulating Mediterranean sophistication.																																																												
<b>Ordering Guide &amp; Finish</b>	15369 TZT - Textured Tannery Bronze™	15393 OZ - Olde Bronze®	15426 BKT - Textured Black																																																												
<b>Housing</b>	Cast Aluminum with tea dust glass	Cast Brass with light linen glass	Aluminum and Brass with light umber glass																																																												
<b>Lamp Base</b>	12V S8 wedge base socket	12V T5 wedge base socket	12V T5 wedge base socket																																																												
<b>Supplied Lamp</b>	18.5-W(VA) 3155K (15599 CLR) Krypton light source Power usage at 12V AC input VA MAX: 18.5-W(VA)	11.6-W(VA) 912X (17023) Xenon light source Power usage at 12V AC input VA MAX: 16.25-W(VA)	11.6-W(VA) 912X (17023) Xenon light source Power usage at 12V AC input VA MAX: 11.6-W(VA)																																																												
<b>Incandescent Lamp Options</b>	N/A	16.25-W(VA) 921X (17025) 6.5-W(VA) 918X (17022) 4-W(VA) 901X (17021)	6.5-W(VA) 918X (17022) 4-W(VA) 901X (17021)																																																												
<b>LED Lamp Options</b>	2W (18036-18038) see page 159 Compares up to 18.5W Krypton	2W (18039-18041) see page 159 Compares up to 16W Xenon	2W (18039-18041) see page 159 Compares up to 16W Xenon																																																												
<b>Wiring</b>	32" of usable #18-2, SPT-1-W leads Cable connector supplied	41" of usable #18-2, SPT-1-W leads Cable connector supplied	34" of usable #18-2, SPT-1-W leads Cable connector supplied																																																												
<b>Mounting Acces. Included</b>	8" In-ground stake	8" In-ground stake	8" In-ground stake																																																												
<b>Optional Acces.</b>	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket																																																												
<b>Notes</b>	U.S. Patent No. D570,517	U.S. Patent Pending	U.S. Patent No. D578,238																																																												
<b>Photometric with Supplied Lamp</b>	<table border="1"> <tr> <td>Distance from Light</td> <td>0'</td><td>1'</td><td>2'</td><td>3'</td><td>4'</td><td>5'</td><td>6'</td><td>7'</td><td>8'</td> </tr> <tr> <td>Footcandles</td> <td>10.13</td><td>4</td><td>.9</td><td>.1</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td> </tr> </table>	Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'	Footcandles	10.13	4	.9	.1	-	-	-	-	-	<table border="1"> <tr> <td>Distance from Light</td> <td>6"</td><td>1'</td><td>2'</td><td>3'</td><td>4'</td><td>5'</td><td>6'</td><td>7'</td><td>8'</td> </tr> <tr> <td>Footcandles</td> <td>8.96</td><td>2.6</td><td>.43</td><td>.13</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td> </tr> </table>	Distance from Light	6"	1'	2'	3'	4'	5'	6'	7'	8'	Footcandles	8.96	2.6	.43	.13	-	-	-	-	-	<table border="1"> <tr> <td>Distance from Light</td> <td>0'</td><td>1'</td><td>2'</td><td>3'</td><td>4'</td><td>5'</td><td>6'</td><td>7'</td><td>8'</td> </tr> <tr> <td>Footcandles</td> <td>10</td><td>5.2</td><td>.8</td><td>.2</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td> </tr> </table>	Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'	Footcandles	10	5.2	.8	.2	-	-	-	-	-
Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'																																																						
Footcandles	10.13	4	.9	.1	-	-	-	-	-																																																						
Distance from Light	6"	1'	2'	3'	4'	5'	6'	7'	8'																																																						
Footcandles	8.96	2.6	.43	.13	-	-	-	-	-																																																						
Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'																																																						
Footcandles	10	5.2	.8	.2	-	-	-	-	-																																																						

Denotes fixture is compatible with incandescent or LED lamps.