

THATCHED
ROOF



AZT

15401 AZT

VINTAGE
PARK™



TZT

15369 TZT

Ordering Guide & Finish	15401 AZT	15369 TZT
Housing	Cast Aluminum with clear glass sprinkler shield	Cast Aluminum with tea dust glass
Lamp Base	12V T3 bi-pin, high temperature porcelain socket	12V S8 wedge base socket
Supplied Lamp	20-W(VA) T3 (17012) Halogen light source Power usage at 12V AC input VA MAX: 20-W(VA)	18.5-W(VA) 3155K (15599 CLR) Krypton light source Power usage at 12V AC input VA MAX: 18.5-W(VA)
Incandescent Lamp Options	10-W(VA) T-3 (17011)	N/A
LED Lamp Options	2W (18042-18044) see page 137. Compares up to 20W Halogen.	2W (18036-18038) see page 137. Compares up to 18.5W Krypton.
Wiring	20" of usable #18-2, SPT-1-W leads. Cable connectors supplied.	32" of usable #18-2, SPT-1-W leads. Cable connectors supplied.
Mounting Access. (Included)	8" In-ground slotted stake	8" In-ground slotted stake
Optional Accessories	15601 – Surface Mounting Flange 15607 – Surface Mounting Bracket	15601 – Surface Mounting Flange 15607 – Surface Mounting Bracket
Notes	U.S. Patent Pending	U.S. Patent No. D570,517
Photometric with Supplied Lamp	Distance from Light	0' 1' 2' 3' 4' 5' 6' 7' 8'
	Foot Candles	9.9 7.3 1.7 .76 .16 – – – –
	Distance from Light	0' 1' 2' 3' 4' 5' 6' 7' 8'
	Foot Candles	10.13 4 .9 .1 – – – –