

I ED	Tapered	1 Cal	lumn
LEU	laptitu		umm



PROJECT:
TYPE:
ORDERING #:
COMMENTS:

FEATURES

- A tapered column rises to a narrow point and then widens to expose LED illumination emanating from the reverse taper cap.
- Cast Aluminum Housing
- 4 W / 5.8 VA Light Output, Integrated LEDs and Driver, 2950K (-150/+175), High CRI
- 9V 15V AC/DC
- 30" of useable #18-2, SPT-1W leads. Cable connector supplied.
- 8" In-ground stake

5"

ORDERING INFORMATION

EXAMPLE: 15804AZT (Product # & Finish)

PRODUCT	FINISH	WATTAGE	LIGHT SOURCE	WIRING	MOUNTING ACCESSORIES (INCLUDED)	OPTIONS & ACCESSORIES
15804 Dimensions: 3" W x 27.25" L	Cast Aluminum AZT - Textured Architectural Bronze™ Fixture Photometric (100 11 21 31 41 72 35 1.4 0.8 0.5	5' 6' 7' 8'	Integrated LEDs and Driver 2950K (-150 / +175) High CRI	30" of usable #18-2, SPT- 1-W leads. Cable connector supplied.	8" In-ground stake	15601AZT - Cast Aluminum Surface Mounting Flange w/ Bronze Finish, Neoprene Gasket For Watertight Seal 15601BKT - Cast Aluminum Surface Mounting Flange w/ Black Finish, Neoprene Gasket For Watertight Seal 15601BBR - Cast Brass Surface Mounting Flange, Neoprene Gasket For Watertight Seal Flange For Tree / Surface Mounting 15607AZT - Textured Bronze Finish 15607BKT - Textured Black Finish 15607BBR - Bronzed Brass Finish



NOTES

For Warranty Information, please visit www.landscapelighting.com

We reserve the right to revise the design or components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.