



15826 AZT, BE, BKT - LED CENTER MOUNT **15870 AZT, BBR, BE, BKT - LED 6" DOME PATH LIGHT**

Description	Unobtrusive, center mount fixture for maximum light spread with the added benefit of LED technology. Coordinates with matching LED deck light 15765 on page 24.	A popular look has a new addition with a smaller 6" shade and is available in LED. Coordinates with our 15810 & 15811 LED Domed Roof series.
Ordering Guide & Finish	15826 AZT - Textured Architectural Bronze (Marine grade powder coat) 15826 BE - Beach (Marine grade powder coat) 15826 BKT - Textured Black (Marine grade powder coat)	15870 AZT - Textured Architectural Bronze (Marine grade powder coat) 15870 BBR - Bronzed Brass 15870 BE - Beach (Marine grade powder coat) 15870 BKT - Textured Black (Marine grade powder coat)
Housing	Cast Aluminum	Cast Aluminum, Cast Brass
Light Source	3 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver	3 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver
Color Temp. (CCT) & CRI	3000K (-200/+125) / 80s CRI	3000K (-200/+125) / 80s CRI
Power Usage at 12V AC Input VA and Watts	4 W, 5.8 VA Multiply fixture VA by the number of fixtures used to determine size of transformer	4 W, 5.8 VA Multiply fixture VA by the number of fixtures used to determine size of transformer
Operating Voltage Range	9V-15V AC/DC with no loss in output due to constant current technology	9V-15V AC/DC with no loss in output due to constant current technology
Lumen Maint.	Tested to an L-70 of 40,000 hours	Tested to an L-70 of 40,000 hours
Total Lumens & Efficacy	3000K = 140 Lm 3000K= 35 Lm/W	3000K = 140 Lm 3000K= 35 Lm/W
Wiring	50" of usable #18-2, SPT-1-W leads. Cable connector supplied	30" of useable #18-2, SPT-1W leads. Cable connector supplied
Mounting Acces. Included	8" in-ground stake	8" In-ground stake
Optional Acces.	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket
Incandescent	15326 - on page 96	15470 - on page 99
Notes	Subjected to Highly Accelerated Life Testing - 3rd party reliability testing Not for use with electronic transformers	Subjected to Highly Accelerated Life Testing - 3rd party reliability testing Not for use with electronic transformers
Fixture Photometric (fc)	Distance from Light 0' 1' 2' 3' 4' 5' 6' 7' 8' Footcandles 8.7 4.7 2.6 1.5 .67 .29 .10 - -	Distance from Light 0' 1' 2' 3' 4' 5' 6' 7' 8' Footcandles 6.11 5.71 3.97 2.55 1.64 0.90 0.50 0.40 0.31