

ABOVE-GROUND



15MHS35 AZT

IN-GROUND



15IGMHS70 AZ

<p>Ordering Guide & Finish</p>	<p>Product ID – 15MHS35 AZT Description – Single 35-W-MH Tap – 120V ANSI# – M130</p>	<p>Product ID – 15IGMHS70 AZ Description – Single 70-W MH Tap – 120V ANSI# – M98</p>
<p>Housing</p>	<p>Stamped steel. Textured Architectural Bronze thermoset powder coat finish. Top and bottom mounting brackets. 1/2" and 3/4" trade size combination knockouts for conduit entry. Stainless steel mounting screws and anchors included.</p>	<p>Single piece Polyphenylene Sulphide (PPS) glass reinforced composite with molded in ribs to prevent ground shift. Two 3/4" NPT entries for conduit attachment. With 1/2" NPSM removable plug for both direct fixture mount and remote mount application. Re-enterable encapsulant 3M 8882 potting compound included. One piece, molded silicone "O" Ring. Stainless steel captive and gasketed screws.</p>
<p>Ballast</p>	<p>Copper wrapped core and coil with High Power Factor (HPF) 105° C High Heat capacitor and long range ignitor. Rated for -20° F starting. Available with single 120V tap.</p>	<p>Quick disconnect ballast with bracket handle. Available with single 120V tap.</p>
<p>Dimensions</p>	<p>Single – 120V: 6.375" W x 9.5" L x 5.25" D</p>	<p>9.625" Dia. X 12" Hgt.</p>
<p>Notes</p>	<p>Above ground ballasts carry a UL listing mark suitable for the US and Canadian marketplace. Maximum distance from lamp to ballast cannot exceed 15' on single (120V) model. Some lamp brands may perform better.</p>	<p>In-ground ballasts carry a CSA listing mark suitable for the US and Canadian marketplace Maximum distance from lamp to ballast cannot exceed 15 feet. Some lamp brands may perform better.</p>