
Shown: 330103NI Brushed Nickel Finish, White Etched Glass with Walnut Blades

$50^{\prime\prime} \,\, \text{Renew}^{\text{T}} \, \text{Select CFL}$







|--|

Blades (5) Included

- 12° Pitch
- 50" Sweep
- Reversible
- Wood

Downrods 4" Downrod with 1" (O.D.)

Downlight Removable. Uses (2) GU24 13-W Non-Dimmable CFL Lamps

Downlight Glass Umber or White Etched

Optional Downlight N/A

Uplight N/A

Uplight Glass N/A

Low Ceiling Adaptable Yes, Flush Mount Canopy Included

Control Pull Chain

FAN FEATURES

Mounting Slope – Pitch 22° or 4/12 Lead Wire 78" cUL Listed Indoor Hanging Weight 27.5 lbs. Warranty Limited Lifetime

MOTOR FEATURES

Motor Size/Type 153mm x 15mm, AC Amps 0.58 on High RPM 203 on High Energy Star N/A

INCLUDED CONTROLS Pull Chain - 3 Speeds - 3 Forward & Reverse - Manual Reverse OPTIONAL CONTROLS



371042MUL (shown) 337001WH 371082

COOLTOUCH™ CONTROL SYSTEM - BASIC See pages 306-308 for more information.

HANGING MEASUREMENTS

WITH 4" DOWNROD				
Fixture Drop (from ceiling)	Blade Drop (from ceiling)	Housing (width)	Ceiling Canopy (width)	←D→
A: 18.40"	B: 10.50"	C: 11.00"	D: 5.90"	
	FLUSH			
Fixture Drop (from ceiling)	Blade Drop (from ceiling)	Housing (width)	Ceiling Canopy (width)	<u>*</u>
A: 14.90"	B: 7.00"	C: 11.00"	D: 5.90"	

AIR PERFORMANCE AIRFLOW POWER AIRFLOW EFFICIENCY USAGE 5518 66 84 Watts on High Cubic Ft. Cubic Ft. Per Minute (Excludes Per Minute Per Watt on High Lights)

Renew [™] Select CI	LFANS 257
------------------------------	-----------