



Shown: 339240MWH Matte White Finish, White Etched Glass with Matte White Blades

50" Renew™ Premier CFL



339240BSS

Brushed Stainless Steel Finish
White Etched Glass
Medium Oak Blades



339240NI

Brushed Nickel Finish
White Etched Glass
Walnut Blades



339240BB

Oil Brushed Bronze™ Finish
White Etched Glass
Cherry Blades



339240BBU

Oil Brushed Bronze™ Finish
Umber Etched Glass
Walnut Blades



339240TZ

Tannery Bronze™ Finish
Umber Etched Glass
Teak Blades



339240WH

White Finish
White Etched Glass
White Blades

BLADE SPECS

Fan Finish Blade Finish & Part Number
(Side 1) (Reversible)

BSS Brushed Stainless Steel	Medium Oak FB339240 BSS	Dark Oak FB339240 BSS
MWH Matte White	Matte White FB339240 MWH	Weathered White Walnut FB339240 MWH
NI Brushed Nickel	Cherry FB339240 NI	Walnut FB339240 NI
OBB Oil Brushed Bronze™	Cherry FB339240 OBB	Walnut FB339240 OBB
OBBU Oil Brushed Bronze™	Cherry FB339240 OBBU	Walnut FB339240 OBBU
TZ Tannery Bronze™	Dark Cherry FB339240 TZ	Teak FB339240 TZ
WH White	White FB339240 WH	

INCLUDED FEATURES

Blades (5) Included

- 12° Pitch
- 50" Sweep
- Reversible
- Wood

Downrods 4" Downrod with 1" (O.D.)

Downlight Integrated. Uses (4) E-26 13-W Non-Dimmable CFL Lamps

Downlight Glass White or Umber Etched

Optional Downlight N/A

Uplight N/A

Uplight Glass N/A

Low Ceiling Adaptable Yes, Flush Mount Canopy Included

Control Pull Chain

FAN FEATURES

Mounting Slope – Pitch 22° or 4/12

Lead Wire 78"

cUL Listed Indoor

Hanging Weight 20.8 lbs.

Warranty Limited Lifetime

MOTOR FEATURES

Motor Size/Type 153mm x 15mm, AC

Amps 0.59 on High

RPM 202 on High

Energy Star N/A

INCLUDED CONTROLS

Pull Chain

- 3 Speeds
- 3 Forward & Reverse
- Manual Reverse



OPTIONAL CONTROLS



371042MUL (shown)
337001WH
371082

COOLTOUCH™ CONTROL SYSTEM – BASIC

See pages 306-308 for more information.


HANGING MEASUREMENTS

WITH 4" DOWNROD

Fixture Drop (from ceiling)	Blade Drop (from ceiling)	Housing (width)	Ceiling Canopy (width)
A: 19.25"	B: 10.50"	C: 11.75"	D: 5.90"

FLUSH MOUNT

Fixture Drop (from ceiling)	Blade Drop (from ceiling)	Housing (width)	Ceiling Canopy (width)
A: 15.75"	B: 7.00"	C: 11.75"	D: 5.90"



AIR PERFORMANCE

AIRFLOW	POWER USAGE	AIRFLOW EFFICIENCY
4898	68	72
Cubic Ft. Per Minute on High	Watts on High (Excludes Lights)	Cubic Ft. Per Minute Per Watt