

LED CEILING

Long-life light emitting diodes (LED) provide approx. 40,000-hour life span to L70 (70% initial lumens) – about 15 years of standard operation.

True optics: pure white light and controlled beam spread with no fade or drop off of light.

High Color Rendering Index (CRI)

Standard installation



These devices comply with part 15 of the FCC Regulations.

LED OUTPUT

| | |
|------------------|--|
| 8112 NILED/OZLED | 1750 LUMENS, 25 WATTS, 3000 KELVIN, CRI 80, 40K LIFE |
| 8116 NILED/OZLED | 1750 LUMENS, 25 WATTS, 3000 KELVIN, CRI 80, 40K LIFE |
| 42379 NI/OZ | 1600 LUMENS, 25 WATTS, 3000 KELVIN, CRI 80, 40K LIFE |
| 42380 NI/OZ | 1600 LUMENS, 25 WATTS, 3000 KELVIN, CRI 80, 40K LIFE |
| 43649 CHLED | 1200 LUMENS, 25 WATTS, 3000 KELVIN, CRI 80, 40K LIFE |
| 43650 CHLED | 1450 LUMENS, 25 WATTS, 3000 KELVIN, CRI 80, 40K LIFE |
| 43845 WHLED | 535 LUMENS, 12 WATTS, 3000/2700 KELVIN, CRI 90, 40K LIFE |
| 43846 WHLED | 850 LUMENS, 15 WATTS, 3000/2700 KELVIN, CRI 90, 40K LIFE |



A | 43875 NILED



A | 43875 OZLED



B | 43876 NILED



B | 43876 OZLED



C | 43877 NILED



C | 43877 OZLED



D | 43883 NILED Hatteras Bay™



D | 43883 OZLED Hatteras Bay™



D | 43883 PNLED Hatteras Bay™



E | 43885 NILED Hatteras Bay™



E | 43885 OZLED Hatteras Bay™



E | 43885 PNLED Hatteras Bay™



F | 42380 NI



F | 42380 OZ



G | 43649 CHLED Savoca™



H | 42379 NI



H | 42379 OZ



J | 43650 CHLED Savoca™



K | 8112 NILED



K | 8112 OZLED



L | 43845 WHLED27



L | 43845 WHLED30



M | 8116 NILED



M | 8116 OZLED



N | 43846 WHLED27



N | 43846 WHLED30

LED CEILING

| | LED ITEM # | FINISH | LIGHT SOURCE | W | H | L | NOTES |
|---|---|------------|--------------|-------|------|-----|---|
| A | 43875 NILED / 43875 OZLED | NI, OZ | 22W | 16 | 3.75 | 16 | Satin Etched Glass. |
| B | 43876 NILED / 43876 OZLED | NI, OZ | 24W | 18 | 3.5 | 18 | Satin Etched Glass. |
| C | 43877 NILED / 43877 OZLED | NI, OZ | 29W | 24 | 3.5 | 24 | Satin Etched Glass. |
| D | 43883 NILED / 43883 OZLED / 43883 PNLED | NI, OZ, PN | 22W | 13.25 | 4.5 | --- | Inside Etched Clear Fresnel Lens. |
| E | 43885 NILED / 43885 OZLED / 43885 PNLED | NI, OZ, PN | 22W | 18 | 5 | --- | Inside Etched Clear Fresnel Lens. |
| F | 42380 | NI, OZ | 25W | 14 | 3.25 | --- | Inside Etched Clear Fresnel Lens. |
| G | 43649 CHLED | CH | 24W | 15 | 6.75 | 15 | Etched White Glass. Dimmable. |
| H | 42379 | NI, OZ | 25W | 13.25 | 3.25 | --- | Opal Etched Glass. |
| J | 43650 CHLED | CH | 24W | 18 | 2.5 | 18 | Etched White Glass. Dimmable. |
| K | 8112 NILED / 8112 OZLED | NI, OZ | 25W | 13.25 | 6 | --- | Satin Etched Glass. Dimmable. |
| L | 43845 WHLED27 / 43845 WHLED30 | WH | 12W | 6 | 1.25 | --- | Frosted Lens. Dimmable. Retrofit ceiling adaptor 4145LED. |
| M | 8116 NILED / 8116 OZLED | NI, OZ | 25W | 15.25 | 6.5 | --- | Satin Etched Glass. Dimmable. |
| N | 43846 WHLED27 / 43846 WHLED30 | WH | 15W | 7.5 | 1.25 | --- | Frosted Lens. Dimmable. Retrofit ceiling adaptor 4146LED. |

Measurements shown in inches. U.S. & Canada Patent Pending: F, G, H, J.

