



# INCANDESCENT/LED 12V HYBRID SPECIALTY



**15415 TZT - CATHEDRAL™ LIGHT RAISED PLANTER**

**15123 BK - MR11 BARBECUE LIGHT**

<b>Description</b>	A tall planter that will allow draped foliage to interplay with the light emitting from within the arched interwoven bands.	Integrated surface mount BBQ light for direct connection to 12V landscape lighting system for rail or outdoor countertop mount only.
<b>Ordering Guide &amp; Finish</b>	15415 TZT - Textured Tannery Bronze™	15123 BK - Black
<b>Housing</b>	Aluminum	Components of durable high heat thermoplastic resin. Lamp shielded by a high heat-resistant flat glass lens sealed for watertight outdoor use. Flexible stem is durable chrome plated steel with heat shrink rubber sleeving. On/off switch is protected by waterproof rubber boot.
<b>Lamp Base</b>	12V T5 wedge base socket 	12V bi-pin, high temperature porcelain socket
<b>Supplied Lamp</b>	16.25-W(VA) 921X (17025) Xenon light source Power usage at 12V AC input VA MAX: 16.25-W(VA)	35-W(VA) MR-11 Halogen light source Power usage at 12V AC input VA MAX: 35-W(VA)
<b>Incandescent Lamp Options</b>	11.6-W(VA) 912X (17023) 6.5-W(VA) 918X (17022) 4-W(VA) 901X (17021)	N/A
<b>LED Lamp Options</b>	2W (18039-18041) see page 159 Compares up to 16W Xenon	N/A
<b>Wiring</b>	27' of usable #18-2, SPT-1-W leads. Cable connector supplied	25' of usable #18-2, SPT-1-W leads. Connector supplied
<b>Mounting Acces. Included</b>	14" In-ground stake	(1) set wood screws and (1) set machine screws and nuts
<b>Photometric with Supplied Lamp</b>	Distance from Light .6' 1' 2' 3' 4' 5' 6' 7' 8'	N/A
	Footcandles 8.87 5.16 1.11 1.84 1.14 0.69 0.46 0.34 0.25	N/A

 Denotes fixture is compatible with incandescent or LED lamps.