



15765 AZT, BBR, BE, BKT, WHT - LED MINI DECK LIGHT

Description	Versatile mini size and simple styling for multiple applications with the added benefit of LED technology.																																
Ordering Guide & Finish	15765 AZT - Textured Architectural Bronze (Marine grade powder coat) 15765 BBR - Bronzed Brass 15765 BE - Beach (Marine grade powder coat) 15765 BKT - Textured Black (Marine grade powder coat) 15765 WHT - Textured White (Marine grade powder coat)																																
Housing	Cast Aluminum or Cast Brass																																
Light Source	2 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver																																
Color Temp. (CCT) & CRI	3000K (-200/+125) / 80s CRI																																
Power Usage at 12V AC Input VA and Watts	1.9W, 2.4 VA Multiply fixture VA by the number of fixtures used to determine size of transformer																																
Operating Voltage Range	9V-15V AC/DC with no loss in output due to constant current technology																																
Lumen Maint.	Tested to an L-70 of 40,000 hours																																
Total Lumens & Efficacy	3000K = 50 Lm 3000K= 26 Lm/W																																
Wiring	72" of usable #18-2, SPT-1-W leads. Cable connector supplied. WHT has coordinating white leads																																
Mounting Acces. Included	Stainless steel mounting bracket																																
Incandescent	15065 - on page 109																																
Notes	Subjected to Highly Accelerated Life Testing - 3rd party reliability testing Not for use with electronic transformers																																
Photometric with Supplied Lamp	<table border="1"> <thead> <tr> <th>Mounting Height</th> <th>0'</th> <th>0.5'</th> <th>1'</th> <th>2'</th> <th>3'</th> <th>4'</th> <th>5'</th> </tr> </thead> <tbody> <tr> <td>6"</td> <td>53.3</td> <td>10.9</td> <td>1.7</td> <td>0.09</td> <td>0.03</td> <td>-</td> <td>-</td> </tr> <tr> <td>12"</td> <td>12.25</td> <td>7.1</td> <td>2.8</td> <td>0.44</td> <td>0.09</td> <td>0.02</td> <td>-</td> </tr> <tr> <td>30"</td> <td>1.9</td> <td>1.8</td> <td>1.4</td> <td>0.72</td> <td>0.33</td> <td>0.14</td> <td>-</td> </tr> </tbody> </table>	Mounting Height	0'	0.5'	1'	2'	3'	4'	5'	6"	53.3	10.9	1.7	0.09	0.03	-	-	12"	12.25	7.1	2.8	0.44	0.09	0.02	-	30"	1.9	1.8	1.4	0.72	0.33	0.14	-
Mounting Height	0'	0.5'	1'	2'	3'	4'	5'																										
6"	53.3	10.9	1.7	0.09	0.03	-	-																										
12"	12.25	7.1	2.8	0.44	0.09	0.02	-																										
30"	1.9	1.8	1.4	0.72	0.33	0.14	-																										