

KOHLER®

Roughing-In

K-1106-H, K-1106-LH, K-1106-RH PROFLEX™ 6032 BATH WHIRLPOOL WITH HEATER

Product Information

Applicable products:	
Bath whirlpool with heater – drop-in	K-1106-H
Bath whirlpool with heater – tile flange, left drain	K-1106-LH
Bath whirlpool with heater – tile flange, right drain	K-1106-RH
Product is ADA compliant when installed with seat at head end ADA	

Fixture*:	
Basin area:	
Bottom area	46" (116.8 cm) x 20" (50.8 cm)
Top area	55" (139.7 cm) x 22" (55.9 cm)
Weight	54 lbs (24 kg)
To overflow:	
Water depth	12-1/2" (31.8 cm)
Capacity	49 gal (185 L)
* Approximate measurements for comparison only.	

Pump:		V	Hz	A
1-speed		120	60	7.5
Heater:	kW	V	Hz	A
	1.5	120	60	12.5

Required Electrical Service

Two dedicated circuits required, each protected with a Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 15 A, 60 Hz
Locate the outlets behind the whirlpool and within 24" (61 cm) of the pump.	

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 37 lbs/square foot (178.7 kg/square meter) loading.

The apron must be installed before the finished floor and wall materials.

This fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-11677 or K-11677M)

