



Purist®

6' Whirlpool Bath

K-1110-M



Features

- 19-1/4" (489 mm) soaking depth.
- End drain.
- Overflows into horizontal overflow drain for maximum bathing depth.
- Coordinates with other products in the Purist collection.
- 72" (1829 mm) x 46" (1168 mm) x 23-3/16" (589 mm)

Material

- Acrylic

Hydrotherapy

- Variable-speed pump for adjusting hydromassage intensity.
- Six fully adjustable Flexjet™ hydrotherapy jets for water flow and direction.
- Two pulsating neckjets with pillows.
- Ten sequencing Bodyssage™ backjets.
- Built-in 1500 W heater.
- Lighted keypad control.
- Remote control.

Installation

- Drop-in or under-mount.

Required Accessories

K-589 Under-mount Installation Kit
K-7273 Bath Drain

Recommended Accessories

K-1601 Bath/Whirlpool Footstop
K-24916 Wireless Music Kit



Codes/Standards




ASME A112.19.7/CSA B45.10
CSA B45.5/IAPMO Z124
ASTM E162
ASTM E662
UL 1795
CSA C22.2 No. 218.2
Greenguard UL 2818 - Gold
CARB P2

KOHLER® One-Year Limited Warranty


See website for detailed warranty information.

Available Color/Finishes

Color tiles intended for reference only.

Color	Code	Description
	0	White
	96	Biscuit
	47	Almond

No change in measurements
with drain shown. (K-7273)



Required Electrical Service

One dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD).

Pump, Heater: 220-240 V, 20 A, 50/60 Hz

Technical Information

All product dimensions are nominal.

Installation:	Drop-in, Under-mount
Drain location:	End
Basin area, bottom:	43" x 26-1/2" (1092 mm x 673 mm)
Basin area, top:	55" x 36" (1397 mm x 914 mm)
Weight:	160 lbs (72.6 kg)
Minimum floor load:	43 lbs/ft² (209.9 kg/m²)
Water depth:	19-1/4" (489 mm)
Water capacity:	96 gal (363.4 L)
Template:	Top-mount/Under-mount, 1016369-7, required, included
Electrical component rating:	Pump: 240 V, 11 A, 50/60 Hz Heater: 240 V, 6.25 A, 1500 W
Pump speed:	Variable

Notes

Measure your actual product for rough-in details.

Install this product according to the installation instructions.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

Pump/piping protrudes beyond rim (see drawing).