

KOHLER® Roughing-In

K-1158-HB, K-1158-HE, K-1158-HJ BANCROFT® 5.5' CUSTOM BATH WHIRLPOOL

Product Information

Applicable product:	
Custom bath whirlpool	K-1158-HB
Custom bath whirlpool	K-1158-HE
Custom bath whirlpool	K-1158-HJ

Fixture*:	
Bathing well:	
Basin area, bottom	46" (116.8 cm) x 30" (76.2 cm)
Basin area, top	57" (144.8 cm) x 34" (86.4 cm)
Weight	130 lbs (59 kg)
To overflow:	
Water depth	16" (40.6 cm)
Capacity	95 gal (359.6 L)
* Approximate measurements for comparison only.	

Pump	Heater	V	Hz	A
	1.5 kW	240	50/60	11

Minimum access panel (required):	
Pump/ control	34" (86.4 cm) W x 15" (38.1 cm) H

No change in measurements if connected with drain illustrated. (K-7161-AF) Jet trim kit K-9698

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD):	
Pump/control	220/240 V, 20 A, 50/60 Hz

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 50 lbs/square foot (816.5 kg/square meter)

Hot water supply should be 70% of capacity or greater. Installations will vary.

This bath is designed for drop-in installation only. It is not suited for use in a three-wall alcove with an overhead shower.

Pump must be relocated to custom position at the time of installation. Provide adequate clearance.

Fixtures conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

