

## Product Information

Applicable products:				
BubbleMassage bath	K-1164-G			
Fixture*:				
Bathing well:				
Basin area, bottom	55-1/4" (140.3 cm) x 23-1/2" (59.7 cm)			
Basin area, top	64-1/2" (163.8 cm) x 32" (81.3 cm)			
Weight	112 lbs (50.9 kg)			
To overflow:				
Water depth	15" (38.1 cm)			
Capacity	75 gal (284.1 L)			
* Approximate measurements for comparison only.				
Included components:				
Cut-out template	1042557-7			
Blower motor	Heater	V	Hz	A
	300 W	120	60	5
Minimum access panel blower motor:				
20" (50.8 cm) W x 15" (38.1 cm) H		required		

## Required Electrical Service

Dedicated circuit required, protected with a Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 5 A, 60 Hz
Locate the outlet behind the bath and within 24" (61 cm) of the blower.	

## Installation Notes

Install this product according to the installation guide.

Floor support under bath must provide for a minimum of 37 lbs/square foot (178 kg/square meter) loading.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-11677 or K-11677M)

Recommended faucet area

