

KOHLER® Roughing-In

K-1122-G ARCHER™ 5' (1.5 m) BUBBLEMASSAGE™ BATH WITH AIRJETS

Product Information

Applicable product:				
Drop-in rim style		K-1122-G		
Fixture*:				
Bathing well:				
Basin area, bottom	45-1/8" (114.6 cm) x 19-11/16" (50 cm)			
Basin area, top	52-3/4" (134 cm) x 25-5/16" (64.3 cm)			
Weight	84 lbs (38.1 kg)			
To overflow:				
Water depth	15" (38.1 cm)			
Capacity	58 gal (219.5 L)			
* Approximate measurements for comparison only.				
Drop-in cutout		58-1/2" (148.6 cm) x 30-1/2" (77.5 cm)		
Blower motor:	Heater	V	Hz	A
	300 W	120	60	5
Required accessories:				
Clearflo slotted overflow brass bath drain OR		K-7271		

Clearflo slotted overflow bath drain – PVC pipe K-7272

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):

Blower motor: 120 V, 15 A, 60 Hz

Blower motor is supplied with a 24" (61 cm) grounding-type plug-in cord.

Installation Notes

Install this product according to the installation guide.

Floor support under this product must provide for a minimum of 45 lbs/square foot (218 kg/square meter) loading.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

A blower motor access panel is required.

This product is designed for a drop-in installation only. It is not suited for use in a three-wall alcove with an overhead shower.

Will comply with **ADA** when installed per Section 607 Bathtubs of the Act.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

