## KOHLER Roughing-In

## K-12634, K-12636, K-12638 MORNINGSIDE™ WHEELCHAIR LAVATORY

## **Product Information**

Applicable product:	
11-1/2" (29.2 cm) centers lavatory less soap dispenser hole	K-12634
11-1/2" (29.2 cm) centers lavatory with soap dispenser hole on left	K-12634-L
11-1/2" (29.2 cm) centers lavatory with soap dispenser hole on right	K-12634-R
4" (10.2 cm) centers lavatory less soap dispenser hole	K-12636
4" (10.2 cm) centers lavatory with soap dispenser hole on left	K-12636-L
4" (10.2 cm) centers lavatory with soap dispenser hole on right	K-12636-R
Single-hole lavatory less soap dispenser hole	K-12638
Single-hole lavatory with soap dispenser hole on left	K-12638-L
Single-hole lavatory with soap dispenser hole on right	K-12638-R

Fixture*:					
Basin area		14" (35.6 cm) x 13" (33 cm)			
Water depth	depth 2-5/		2-5/8″ (6.7 cm)		
Drain hole		1-3/4" (4.4 cm) D.			
*Approximate measurements for comparison only.					
Holes	K-12634		K-12636	K-12638	
Spout	1-3/8″ (3.5 cm) D.		1-1/4″ (3.2 cm) D.	1-3/8″ (3.5 cm) D.	
Faucet	1-3/8″ (3.5 cm) D.		1-1/4″ (3.2 cm) D.		
Soap dispenser	1-1, (3.2	/4″ ? cm) D.	· · ·		

## **Installation Notes**

Concealed arm carrier required, **NOT** supplied by Kohler Co. Will comply with **ADA** when installed per Section 606 Lavatories of the Act.

Will comply with **CSA B651** when installed per Clause 4.3.3 of the standard.

Will comply with **OBC** when installed per Clause 3.8.3.11. Fixture conforms to ASME Standard A112.19.2/CSA B45.1. All dimensions are nominal.



