# **KOHLER**, Faucets

# Gooseneck Insight™

DM Faucet w/Mixer K-13474

#### **Features**

- 0.5 gal/min (1.9 l/min) flow rate.
- Factory set 30 second max. continual run cycle.
- Vandal-resistant aerator.
- 24" (610 mm) flexible supply hoses for easy installation.
- 6-3/16" (157 mm) spout reach.
- Less drain.

#### Material

Brass Construction.

## **Technology**

- Requires an AC power supply.
- Electronic Insight<sup>™</sup> Sensor Technology for accurate and consistent activation.

#### Installation

- Single-hole mounting.
- Above-counter valve for easy installation and maintenance.
- 13480-A or 13481-A power supplies are designed for North America outlets

# **Required Accessories**

K-13480-A

or

K-13481-A

or

K-13480 AC Single Supply

or

K-13481 Multi-outlet Power Supply

#### **Optional Accessories**

1160593 .35 gpm Aerator, Small

1049937 Small Spray 0.5 gpm (1.9 l/min)

1139286 Small Aerated 1.0 gpm (3.8 l/min)

1139287 Small Laminar 1.0 gpm (3.8 l/min)

1053576 Small Aerated 1.5 gpm (5.7 l/min)

1053532 Small Laminar 1.5 gpm (5.7 l/min)

78783 Sealing Washer



ADA CSA B651 OBC

#### Codes/Standards

ASME A112.18.1/CSA B125.1

NSF 372

All applicable US Federal and State material

regulations

DOE - Energy Policy Act 1992

ADA

ICC/ANSI A117.1

CSA B651

OBC

### **KOHLER® One-Year Limited Warranty**

See website for detailed warranty information.

#### **Available Color/Finishes**

Color tiles intended for reference only.

**Color Code Description** 


CP Polished Chrome





# Gooseneck Insight™

DM Faucet w/Mixer K-13474



### **Technical Information**

All product dimensions are nominal.

Valve body: Machined Brass

Faucet:

Flow rate: 0.5 gal/min (1.9 l/min)

#### **Notes**

Install this product according to the installation guide.

A 1-1/4" (32 mm) minimum to 1-1/2" (38 mm) maximum diameter mounting hole is required.

The minimum distance between the back of the faucet spout and the wall must be 1-3/4" (44 mm). This will allow proper clearance for setscrew access.

The maximum distance between the bathroom sink basin edge to the base of the faucet spout must be 1-3/4" (44 mm).

The maximum height of the lip basin should be 3/4" (19 mm).

Product includes rosebud spray aerator Other aerator styles are available. Please contact your distributor or see Kohler.com.

This product requires an AC power supply (not included).

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.

